





	<a href="#">EXTENDER HDMI+USB-EX-70-4K-PRO</a>	<a href="#">EXTENDER EXT-POE2 PULSAR</a>	<a href="#">WI-FI SMART PLUG ATLO-P1U2-TUYA Wi-Fi, Tuya Smart</a>	<a href="#">ADAPTER BNC-W/CINCH-G*P100</a>
				
	73.12 CHF 73.12 CHF	28.12 CHF 28.12 CHF	11.23 CHF 11.23 CHF	21.00 CHF 21.00 CHF
Supported HDMI resolutions	max. 4K UHD @ 30 Hz	...	...	...
Rated voltage	...	...	100 ... 240 V	...
Maximal total load	...	...	2300 W	...
Standards	...	PoE : IEEE 802.3at, IEEE 802.3af	...	...
In package	...	...	...	<b>100 pcs The price for package</b>
Input voltage	...	42 ... 57 V DC	...	...
Output voltage	...	42 ... 57 V DC	...	...
Number of inputs	...	1	...	...
Total maximal current	...	...	<ul style="list-style-type: none"> <li>• 10 A @ 230 V AC</li> <li>• 2 x 1 A @ 5 V DC</li> </ul>	...
Number of outputs	...	2	...	...
Connector	...	3 x RJ-45 socket	...	...
Connector type	...	...	...	Adapter BNC Plug / CINCH Socket
LED indicators	...	Link/Act	...	...
Attachment of connector elements	...	...	...	—
Maximal transmission range	<ul style="list-style-type: none"> <li>• 40 m - UTP cat. 6, 6A, 7 @ 4K UHD,</li> <li>• 70 m - UTP cat. 6, 6A, 7 @ 1080p</li> </ul>	...	...	...
Impedance	...	...	...	75 Ω
Material	...	...	...	Metal
Number of outlets	...	...	<ul style="list-style-type: none"> <li>• 1 pcs - 230 V AC,</li> <li>• 2 pcs - 5 V DC USB</li> </ul>	...
Socket type	...	...	<ul style="list-style-type: none"> <li>• CEE 7/3 (Schuko),</li> <li>• 2 x USB-A</li> </ul>	...
Plug type	...	...	CEE 7/7	...
Supported data rates	...	<ul style="list-style-type: none"> <li>• Range : 100 m - Input, 100 m - 2 x Output,</li> <li>• Supported data rates : 10 / 100 Mbps - Fast Ethernet</li> </ul>	...	...
Grounding	...	...	✓	...
Wireless	...	...	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	...
Output power	...	max. 15.4 W / port PoE max. 20 W (total)	...	...

Main features	<ul style="list-style-type: none"> <li>• Extender also allows to extend an USB 2.0 port, eg. in order to control the recorder using the mouse</li> <li>• Support KVM function,</li> <li>• HDMI 1.4</li> <li>• HDCP 1.4</li> <li>• HDR support,</li> <li>• Audio: DTS, DTS-HD, PCM, LPCM support</li> <li>• PoC support - only TX power supply is needed</li> <li>• ESD protection - IEC 61000-4-2, ±4kV contact, ±8kV air</li> </ul>	...	...	...
Mobile phones support	...	...	<ul style="list-style-type: none"> <li>• The <a href="#">Tuya Smart</a> free application on Android</li> <li>• The <a href="#">Tuya Smart</a> free application on iOS</li> </ul>	...
Protections	...	<ul style="list-style-type: none"> <li>• Overvoltage</li> <li>• Overload</li> <li>• Short-circuit</li> </ul>	...	...
Operation temp. / Relative humidity	...	-10 ... 40 °C / 10 ... 90 %	...	...
Power supply	5 V DC / 2 A (power adapter included)	...	...	...
Manufacturer / Brand	...	PULSAR	...	...
Main features	<ul style="list-style-type: none"> <li>• Very good image quality with no visible distortions caused by compression,</li> <li>• No delays in video transmission,</li> <li>• No delays in mouse control operations</li> <li>• Designed to continuous operation 24/7</li> <li>• USB-A / USB-A cable included</li> </ul>	...	<ul style="list-style-type: none"> <li>• schedule,</li> <li>• timer,</li> <li>• remote access,</li> <li>• voice control</li> <li>• Easy operation</li> <li>• ON/OFF button</li> <li>• STATUS indicator</li> </ul>	<ul style="list-style-type: none"> <li>• Very easy and quick assembly</li> <li>• Corrosion resistance</li> </ul>
Housing	...	Metal	Plastic	...
Color	...	...	White	...
Operation temp	-20 °C ... 60 °C	...	-20 °C ... 50 °C	...
Permissible relative humidity	0 % ... 90 % (non-condensing)	...	≥ 80 %	...
Weight	<ul style="list-style-type: none"> <li>• 0.12 kg - Transmitter</li> <li>• 0.13 kg - Receiver</li> </ul>	0.11 kg	0.13 kg	0.008 kg
Dimensions	77 x 60 x 20 mm - Transmitter or receiver dimensions	81 x 77 x 26 mm	121 x 52 x 70 mm	Ø 15 x 30 mm
Guarantee	2 years	2 years	2 years	2 years