




	OMNIDIRECTIONAL ANTENNA MEGA-CAMP	NVR BCS-NVR1602-4K-II 16 CHANNELS	POWER SUPPLY ADAPTER PSC-12010/PRO 12 V DC 1 A
			
	23.34 GBP 23.34 GBP	305.10 GBP 305.10 GBP	6.19 GBP 6.19 GBP
Standard	...	TCP/IP	...
Adapter type	Switching
Output voltage	12 V DC
Maximal load	1 A
Average active efficiency	83 %
Output power	12 W
Receiving channels	<ul style="list-style-type: none"> • 6 ... 12, • 21 ... 48
Power consumption at no-load	< 0.1 W
Number of outputs	1 pcs
Gain	20 ... 33 dB, 44 dB (max)
Power connectors type	2.1/5.5 mm - Straight plug
Power voltage	100 ... 240 V AC
Housing type	Plastic
"Index of Protection"	IP67
Frequency range	<ul style="list-style-type: none"> • 174 ... 230 MHz, • 470 ... 698 MHz
Polarization	Horizontal
Impedance	75 Ω
Supported resolutions	...	16 @ 4000 x 3000 px, 16 @ 3840 x 2160 px, 16 @ 3072 x 2048 px, 16 @ 2592 x 1944 px, 16 @ 2048 x 1536 px, 16 @ 1920 x 1080 px, 16 @ 1280 x 960 px, 16 @ 1280 x 720 px,	...
Video outputs	...	1 pcs HDMI 1 pcs VGA	...
Audio support	...	16 Channels - Audio from cameras	...
Audio inputs	...	1 pcs External microphone input - CINCH	...
Audio outputs	...	1 pcs CINCH	...
Image compression method	...	H.265 / H.264 / MJPEG	...
Main features	<ul style="list-style-type: none"> • Reception angle : 360 ° • Length of the cable : 5.80 m and 0.45 m • Diode voltage indicator • High resistance to wind and weather • Very easy installation • Antenna cable + F plug, Antenna separator + IEC plug, Power supply cable + USB-A plug, base for mounting the antenna, Mast mounting diameter, U-Bolt - included • Mast diameter : max. 35 mm • DVB-T/T2 (VHF, UHF), DAB+ 	...	<ul style="list-style-type: none"> • Short-circuit protection • Overload protection • The device has very small dimensions • Length of the cables : 40 + 15 cm

Maximal total frame rate	...	400 fps @ 4000 x 3000 px, 400 fps @ 3840 x 3160 px, 400 fps @ 3072 x 2048 px, 400 fps @ 2592 x 1944 px, 400 fps @ 2048 x 1536 px, 400 fps @ 1920 x 1080 px, 400 fps @ 1280 x 960 px, 400 fps @ 1280 x 720 px,	...
Supported hard drives	...	2 x 6 TB SATA III	...
Recording modes	...	Manual, Sensor, Motion detection, Schedule	...
Network protocols	...	HTTP, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server	...
External storage devices backup	...	Backup to USB drive (pendrive, external drive)	...
Searching and playback the records	...	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) All channels synchronous playback, Smart Search function	...
Bitrate	...	max. 192 Mbps	...
Network functions	...	Full support via network, Remote records copying, Web-Server built-in max. 128 on-line users	...
ONVIF	...	✓	...
Mobile phones support	...	Port 37777 • Android: Free application DMSS • iOS (iPhone): Free application DMSS	...
Default IP address	...	192.168.1.108	...
Default admin user / password	...	admin / admin	...
Web browser access ports	...	80, 37777	...
PC client access ports	...	37777	...
Mobile client access ports	...	37777	...
Operation temp	...	-10 °C ... 55 °C	0 °C ... 40 °C
RTSP URL	...	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
Alarm inputs / outputs	...	4 pcs / 2 pcs - Relay output	...
PTZ control	...	RS-485 - Many protocols	...
Motion Detection	...	22 x 18 motion zones	...
Intelligent image analysis	...	✓	...
Mouse support	...	✓	...
IR remote controller in the set	...	—	...
Power supply	5 V DC, 30 mA USB-A plug	12 V DC / 4 A (power adapter included)	...
Weight	0.28 kg	1.69 kg (without HDD)	0.12 kg
Dimensions	Ø 263 x 54 mm	375 x 285 x 56 mm	57 x 40 x 26 mm
Supported languages	...	English, Polish	...
Country of origin	...	China	...
Manufacturer / Brand	WIEDYSKA	BCS	...
Guarantee	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00