

	CRIMP PLUG BNC-W/ZAC-H155	COMPRESSION PLUG BNC-W/4879*P10 RG6 NS100 Triset113
		
	5.62 DKK 5.62 DKK	48.24 DKK 48.24 DKK
In package	...	10 pcs The price for package
Connector type	BNC Straight plug	BNC Plug
Attachment of connector elements	Crimping	Compression mounting
Application	Coaxial cable	Coaxial cable
Impedance	50 Ω	...
Wire mounting	Crimping	Pressing
Material	Metal	...
Dielectric diameter	...	max. 4.8 mm
Cable diameter	max. 6.1 mm	max. 7.9 mm
Shield fastening	Crimping	Compression mounting
Watertightness	...	✓
Example of application	• TRI-LAN/100 • H-155	• RG6, • NS100-TRISHIELD • Triset113
Main features	• Wide frequency range • Corrosion resistance • To crimp use the crimping tool HT-301C	• Properly compressed connection is highly resistant to break • Watertightness of connector with cable connection • Very easy and quick assembly • Corrosion resistance • Very low loss in the whole operating band • To crimp use the crimping tool HT-5082R
Weight	0.01 kg	0.013 kg
Dimensions	Ø 14 mm x 30 mm	Ø 14.5 mm x 39 mm
Guarantee	2 years	2 years