








	TV OR MONITOR MOUNT BRATECK-FS22-44TF	EXTENDER USB-EX-200	TV OR MONITOR MOUNT BRATECK-LPA39-223	HUB USB 3.0 H1208A	ENCLOSURE LOCK TPR- ZAM	ACCESS POINT 4G+ LTE +ROUTER RUT361 2.4 GHz 300 Mbps Teltonika	TV OR MONITOR MOUNT AX-SATURN RED EAGLE
							
	340.30 DKK 340.30 DKK	361.93 DKK 361.93 DKK	116.99 DKK 116.99 DKK	38.83 DKK 38.83 DKK	29.41 DKK 29.41 DKK	1470.68 DKK 1470.68 DKK	165.71 DKK 165.71 DKK
Application	...	...	...	...	TPR enclosures	...	...
Frequency range	...	...	...	...	...	2.4 GHz	...
Thread type	...	...	...	...	M16	...	...
Bolt length	...	...	...	...	28 mm	...	...
Connectors	...	• USB • RJ45	...	• 1 x plug - USB-A • 4 x socket - USB-A	...	...	...
Distance of the bolt from the lock	...	...	...	...	11.5 mm	...	...
Length of the cable	...	...	...	18 cm	...	...	...
Material	...	...	...	...	Nickel	...	...
USB standard	...	...	...	3.0	...	...	...
Range	...	• 50 m - USB 2.0, • 100 m - USB 1.1	...	...	...	...	...
Antenna type	...	...	...	...	...	2x2 MIMO : 2 x Omnidirectional antenna Wi-Fi - 5 dBi (SMA connector) , 2 x Omnidirectional antenna 4G LTE - 4 dBi (SMA-RP connector)	...
UTP category	...	5e / 6	...	...	...	...	...
Mounting standard	VESA : 100 x 100, 200 x 100, 200 x 200, 300 x 200, 300 x 300, 400 x 200 400 x 300, 400 x 400	...	VESA 75, 100, 200x100, 200	...	...	...	VESA 75, 100, 200, 200 x 100, 300, 400 x 200, 400
Standards	...	...	...	...	...	IEEE 802.11 b/g/n, 4G+ Cat.6 LTE, 3G	...
Screen size range	32 " ... 55 "	...	23 " ... 42 "	...	...	...	23 " ... 56 "
Bearing capacity	35 kg	...	35 kg	...	...	...	45 kg
Distance from mounting surface	...	...	45 ... 508 mm	...	...	...	81 ... 360 mm
Color	Black	...	Black	...	...	...	Black
Tilt adjustment	-10 ° ... 10 °	...	-15 ° ... 10 °	...	...	...	-12 ° ... 12 °
Horizontal rotation	—	...	-90 ° ... 90 °	...	...	...	-90 ° ... 90 °
Rotation in the plane of the screen	—	...	± 3 °	...	...	...	—
Baud rates	...	...	...	...	...	11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 300 / 42 Mbps (4G / 3G)	...
LAN ports	...	...	...	...	...	• 1 x 10/100 Mbps - WAN • 1 x 10/100 Mbps - LAN	...
Transmitter power	...	...	...	...	...	≤ 17.51 dBm @ 2.4 GHz ≤ 23 dBm @ 4G LTE ≤ 24 dBm @ 3G WCDMA	...
LED indicators	...	...	...	...	...	Power, WAN, WLAN, LAN, LTE - 3G/4G, Signal indicator	...
Network type	...	...	...	...	...	4G, 3G	...
LTE	...	...	...	...	...	✓	...
QSS	...	...	...	...	...	—	...
WDS	...	...	...	...	...	—	...
DHCP server	...	...	...	...	...	✓	...
Protections	...	...	...	...	...	• WPA3-EAP • WPA3-SAE • WPA2-Enterprise - PEAP • WPA2-PSK • AES-CCMP • WEP • TKIP • Auto Cipher modes • Client separation • SSID hiding • MAC addresses filtering	...
Management interface	...	...	...	...	...	Web browser, Teltonika RMS application, SMS	...

Main features	Adjustable shelf height in the range of 60 cm	...	...	Solid workmanship	2 keys included	<ul style="list-style-type: none"> <li>• Support for IoT (Internet of Things) systems,</li> <li>• Ability to work as a Hotspot,</li> <li>• Support for VoIP technology,</li> <li>• Support for Mesh technology</li> <li>• SIM socket</li> <li>• DHCP Relay support</li> <li>• DHCP client list</li> <li>• Static / dynamic routing</li> <li>• VPN support</li> <li>• Default address : 192.168.1.1</li> <li>• Configuration using the Teltonika RMS application</li> <li>• WAN Connection Backup - thanks to the fully functional WAN / LAN port, you can use various types of backup connections, including cable, fiber and DSL modems</li> </ul>	...
Power supply	...	...	...	...	...	<ul style="list-style-type: none"> <li>• 12 V DC / 1.5 A (power adapter included)</li> <li>• 9 ... 30 V DC</li> </ul>	...
Power consumption	...	...	...	...	...	≤ 4.7 W	...
Operation temp	...	...	...	...	...	-40 °C ... 75 °C	...
Permissible relative humidity	...	...	...	...	...	10 % ... 90 % (non-condensing)	...
Weight	12 kg	0.05 kg (total)	2.7 kg	0.03 kg	0.022 kg	0.25 kg	4.02 kg
Dimensions	1170 ... 1470 x 600 x 400 mm	61 x 30 x 20 mm	226 x 229 x (45 ... 508) mm	88 x 17 x 9 mm	39 x 20 x 22 mm	100 x 93 x 30 mm	433 x 150 x (81 ... 360) mm
Manufacturer / Brand	BRATECK	...	...	UNITEK	...	Teltonika	RED EAGLE
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years