





	VANDALPROOF CAMERA DP-954HHD/IRD STANDARD: PAL, 1000 TVL 2.8 mm	TV OR MONITOR MOUNT AX-TYTAN-ALUXX	TOGGLE PLUG DUOTEC-10/SPH Fischer	TV OR MONITOR MOUNT BRATECK-LPA68-221
				
	73.06 CAD 73.06 CAD	156.99 CAD 156.99 CAD	1.67 CAD 1.67 CAD	10.80 CAD 10.80 CAD
Standard	PAL
Sensor	1/3 " Sony EXMOR CMOS
Material	<ul style="list-style-type: none"> • Toggle Plug, Nylon • Screw, Steel galvanized 	...
Matrix size	1.3 Mpx
Drilling diameter	10 mm	...
Resolution	1000 TVL
Expansion plug length	40 mm	...
Lens	2.8 mm
Mounting standard	...	VESA : 200, 300, 400 x 200, 400, 600 x 400	...	VESA : 100, 200, 200x100
Screw dimensions	Ø 5 x 60 mm	...
Screen size range	...	37 " ... 70 "	...	23 " ... 43 "
Bearing capacity	...	45 kg	...	30 kg
Mounting panel thickness	9.5 ... 55 mm	...
View angle	<ul style="list-style-type: none"> • 81 ° (manufacturer data) • 90 ° (our tests result)
Cavity depth	min. 40 mm	...
Range of IR illumination	20 m
Distance from mounting surface	...	54 ... 448 mm	...	56 ... 204 mm
Video output	1 Vpp 75 Ω
Power supply	12 V / 270 mA
Tilt adjustment	...	-15 ° ... 15 °	...	-8 ° ... 5 °
Horizontal rotation	...	-60 ° ... 60 °	...	-90 ° ... 90 °
Application	<ul style="list-style-type: none"> • plasterboard • Gypsum fibreboard • OSB board • MDF board • Concrete • Solid clay brick • Solid sand-lime brick 	...
Rotation in the plane of the screen	...	± 3 °	...	—
Manufacturer / Brand	Fischer	BRATECK

Main features	<ul style="list-style-type: none"> • ICR - Movable InfraRed filter • DNR - Digital Noise Reduction • WDR - Wide Dynamic Range • Privacy zones - max. 8 • Motion Detection - max. 4 zones • Mirror - Mirror image • Auto White Balance • Sharpness - sharper image outlines • Day/Night mode (color/b&w/auto)
OSD menu	✓
Vandal-proof	✓
Housing	Dome - Metal
Color	Black	Silver / Black	...	Black
"Index of Protection"	IP65
Operation temp	-10 °C ... 45 °C
Weight	0.37 kg	4.76 kg	...	1.03 kg
Dimensions	Ø 94 x 70 mm	720 x 435 x (54 ... 448) mm	...	230 x 230 x (56 ... 205) mm
Guarantee	2 years	2 years	2 years	2 years