




	ACCESS POINT 4G LTE +ROUTER TL-MR6400 300Mb/s TP-LINK	ACCESS POINT +ROUTER ARCHER-VR300 VDSL / ADSL 2.4 GHz, 5 GHz 300 Mbps + 867 Mbps TP-LINK	CABLE 2C-W/J-W2.5-1.5MB 1.5 m
			
	77.35 EUR 77.35 EUR	64.17 EUR 64.17 EUR	3.30 EUR 3.30 EUR
Frequency range	2.4 GHz	2.4 GHz, 5 GHz	...
Cable	2 x CINCH Plug / JACK 2.5 mm Plug STEREO
Length of the cable	1.5 m
Antenna type	2 x WiFi built-in , 2 x 4G LTE - 2 x SMA socket - Possibility to connect the wire antenna	4 x Omnidirectional antenna 5 dBi	...
Standards	802.11n/g/b IEEE 802.3/3u	IEEE 802.11 b/g/n, IEEE 802.11 a/n/ac, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab ITU G.993.2, ITU-T G.993.5 (G.vector), ITU-T G.998.4 (G.INP), Full-rate ANSI T1.413 Issue 2, ITU-T G.992.1(G.DMT), ITU-T G.992.2(G.Lite), ITU-T G.994.1 (G.hs), ITU-T G.995.1, ITU-T G.992.3 (G.DMT.bis), ITU-T G.992.4 (G.lite.bis), ITU-T G.992.5	...
Modulation type	DBPSK, DQPSK, CCK OFDM, 16-QAM, 64-QAM
LAN ports	• 1 x 10/100 Mbps - LAN/WAN • 3 x 10/100 Mbps - LAN	• 1 x 10/100 Mbps - LAN/WAN, • 3 x 10/100 Mbps - LAN	...
LED indicators	...	Power, DSL, INTERNET, WLAN, LAN	...
Receiver sensitivity	• 11g 54M: -74dBm • 11n HT20: -71dBm • 11n HT40: -67dBm
LTE	✓
QSS	✓
WAN interface	...	• 1 x RJ-11, ADSL / ADSL2 / ADSL2+ / VDSL / VDSL2 • 1 x RJ-45	...
WDS	✓
Transmitter power	...	< 20 dBm @ 2.4 GHz , < 23 dBm @ 5 GHz	...

Baud rates	11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 150 Mbps	300 Mbps @ 2.4 GHz + 867 Mbps @ 5 GHz	...
DHCP server	...	✓	...
Firmware update	...	✓	...
DDNS	...	• DynDNS • No-IP	...
Operation modes	...	ADSL/VDSL modem, Router, Access Point, Bridge WDS	...
Protections	...	• LAN : NAT, SPI network firewall, Access control, IP- MAC Binding, Support DoS defence, parental control • WLAN : WEP 64/128-bit, WPA/WPA2, WPA- PSK/WPA2-PSK, QSS (Quick Secure Setup) - WPS	...
Management interface	...	Web browser, TP-LINK Tether	...

Main features	<ul style="list-style-type: none"> • SIM socket • WPS/RESET button 	<ul style="list-style-type: none"> • Enable/disable wireless network • SSID hiding • QoS • WMM (Wi-Fi Multimedia), • Rate limit • Internet access filtering • Wireless transmission statistics • Firewall • Remote management • DHCP : DHCP server, DHCP client list • Port forwarding : Virtual Server, Port Triggering, DMZ, ALG, UPnP • VPN networks: IPsec VPN, L2TP VPN, PPTP VPN, VPN Pass-through • IPv6 compliance • Static / dynamic routing • Port Mapping • IGMP Snooping V1/V2/V3 • Guest Network - a separate and secure network for guests • Built-in 4-port switch • ON/OFF button • WPS button • The WPS function allows to easy establish an encrypted connection • RESET button • The DSL line splitter included 	<ul style="list-style-type: none"> • Very easy and quick assembly
Power supply	9 V DC / 1 A (power adapter included)	12 V DC / 1 A (power adapter included)	...
Operation temp	0 °C ... 40 °C	0 °C ... 40 °C	...
Permissible relative humidity	max. 95 % (non-condensing)	10 % ... 90 %	...
Weight	0.354 kg	0.31 kg	0.050 kg
Dimensions	202 x 141 x 34 mm	257 x 160 x 37 mm	...
Manufacturer / Brand	TP-LINK	TP-LINK	...
Guarantee	3 years	2 years	2 years