

	SWITCH POE TL-SG3210XHP-M2 8-PORT SFP TP-LINK	U-BOLT CLAMP OZ-50/M8
		
	534.87 EUR 534.87 EUR	1.14 EUR 1.14 EUR
Material	...	Metal
Mast diameter	...	max. 50 mm
U-bolt diameter	...	Ø 8 mm
LAN ports	<ul style="list-style-type: none"> • 8 x RJ45 100/1000/2500 Base-TX, • 2 x port SFP+ - Uplink 1000 Base-X / 10 Gigabit Ethernet, • 1 x RJ45 - Console, • 1 x micro USB - Console 	...
Management	✓	...
Transmission speed	<ul style="list-style-type: none"> • 100 / 1000 / 2500 Mbps - 8 LAN & PoE ports, • 10 Gb/s - 2 SFP ports 	...
Maximal output power	30 W / port PoE	...
Maximal total power	240 W	...
Jumbo Frame	9 kB	...
MAC addresses table	16k	...

Main features	<ul style="list-style-type: none"> • Omada Central Management System • Software Omada Controller • Support for Access Point Wi-Fi 6 • Switch is managed via a web browser, command line interface and SNMP, RMON protocols • CoS/DSCP priority based on IEEE 802.1p standard • Queue scheduling: SP, WRR, SP+WRR • Port/flow-based rate limiting • Static link aggregation • Spanning Tree STP/RSTP/MSTP • BPDU Filtering/Guard • TC / Root Protect • Loop back detection • Data Flow Control (802.3x) • Port mirroring function • IPTV compliance • IGMP Snooping V1/V2/V3 • MLD Snooping V1/V2 • IEEE 802.1Q VLAN, Port Based VLAN, MAC Based VLAN, Private VLAN support • IEEE 802.1Q standard support, up to 4096 VLAN groups and 4K VIDs • GVRP (GARP VLAN Registration Protocol) support • Access Control List - ACL package filtering based on source and destination MAC addresses • Hardware supports IP + MAC binding based on port • DHCP snooping support • Support DoS defence • Storm Control function • IEEE 802.1x and Radius Authentication • Port isolation • SSL, SSH • IPv6 compliance • Multicast • Static routing • DHCP server • DHCP client • System logs • Group control • Reboot schedule • MIB support • Console : RJ-45 output, micro USB 	<ul style="list-style-type: none"> • The whole galvanized • Plate thickness : 2.5 mm
---------------	---	--



LED diodes	<ul style="list-style-type: none"> • Power, System, PoE Max, Fan • Link/Act • 100/1000 Mbps Speed, 2.5 Gb/s Speed - 1 ... 8 ports • 1 Gb/s Speed, 10 Gb/s Speed - 9, 10 ports • PoE, Over Budget, FAULT - 1 ... 8 ports 	...
Housing	Metal	...
Operation temp	0 °C ... 50 °C	...
Certificates	CE, FCC, RoHS	...
Power supply	100 ... 240 V AC	...
Power consumption	max. 17.24 W @ 110 V max. 291.49 W @ 110 V (PoE)	...
Weight	2.2 kg	...
Dimensions	440 x 180 x 44 mm, RACK 19", 1U	80 x 90 x 23 mm
Manufacturer / Brand	TP-LINK	DELTA
Guarantee	5 years	3 years