

| | IP CAMERA IPC-HDW240TM-S-LI-Q280R WisSense - 8.3 Mpx 4K UHD 2.8 mm DAHLIA | MOUNTING BRACKET FOR MOUNTING THE RECORDER IN THE BACK CABINET DM-LU-S80 UNIVIEW | KRONE BACKMOUNT FRAME ISA.GN.105 | TV OR MONITOR MOUNT AX-FLEX-42 | LVLS WIRE METAL AND WOOD DETECTOR UT-387E UNILT | DATA SINGLE SOCKET OUTLET WITH SOCKET ACCESS ELEMENT GN: DATA-PLS System 43 | CABLE PROTECTOR RATIO: KP-16X100 | VOLTAGE CONVERTER DCDC1131515-5A | SWITCHING ADAPTER FIBRE-IRS-POWERSUPPLY |
|-------------------------------------|--|--|----------------------------------|---|---|---|----------------------------------|--|---|
| | | | | | | | | | |
| Material | 7891.49 CZK 7891.49 CZK | 207.71 CZK 207.71 CZK | 96.18 CZK 96.18 CZK | 169.91 CZK 169.91 CZK | 1062.52 CZK 1062.52 CZK | 124.91 CZK 124.91 CZK | 157.71 CZK 157.71 CZK | 372.87 CZK 372.87 CZK | 539.74 CZK 539.74 CZK |
| Standard | TCP/IP | | | | | | Stainless steel | | |
| Adapter type | | | | | | | | | Switching |
| Application | | UNIVIEW recorders of the NVR812 series | | | | System 45 | | | |
| Number of mounted profile modules | | 5 pcs | | | | | | | |
| Type | | | | | | | | Increasing the voltage, DC/DC | |
| Sensor | 1/2.7" Progressive Scan CMOS | | | | | | | | |
| Type of mounted profile modules | | | 10PAR | | | | | | |
| Matrix size | 8.3 Mpx | | | | | | | | |
| Rated voltage | | | | | | 230 V / 50 Hz | | | |
| Power voltage | | | | | | | 11 ... 14.5 V DC | 100 ... 240 V AC | |
| Frequency range | | | | | | | | 50/60 Hz | |
| Maximal current load | | | | | | 16 A | | | |
| Mounting standard | | | | VESA 75, 100, 200 x 100, 200 | | | | | |
| Grounding | | | | | | ✓ | | | |
| Maximal load | | | | | | | | | 1.2 A |
| Cable terminals | | | | | | | screw terminals | | |
| Screen size range | | | | 13" ... 42" | | | | | |
| Socket type | | | | | | | CEE 7/5 | | |
| Bearing capacity | | | | 25 kg | | | | | |
| Protection shutter | | | | | | | | | |
| Distance from mounting surface | | | | 56 ... 230 mm from wall | | | | | |
| Detector range | | | | | <ul style="list-style-type: none"> • Wood : 38 mm, • Non-ferromagnetic metal : 80 mm, • Ferromagnetic metal : 100 mm, • AC live wires : 40 mm | | | | |
| Output voltage | | | | | | | | 15 V, 16 V, 18 (18.5) V, 19 (19.5) V, 20 V, 22 V, 24 V DC -selectable by switch | 20 V DC |
| Power | | | | | | | 90 W | | 24 W |
| Tilt adjustment | | | | 5° ... 15° | | | | | |
| Application | | | | | | | | <ul style="list-style-type: none"> • Device is dedicated to power laptops • cameras • monitors | FibreIRS optical kit |
| Horizontal rotation | | | | Articulated arm with two swivels in range -90° ... 90° each | | | | | |
| Rotation in the plane of the screen | | | | | | | | | |
| Output | | | | | | | | 10 pcs 6.50/4.40mm, 2 x 5.50/2.50mm, 3 x 5.0/1.35mm, 6.30/3.00mm, 2 x 4.80/1.70mm, 5.50/3.00mm, 7.40/5.00mm, 8.0/5.50mm | 2,1/5,5 mm plug |
| Main features | | | | | <ul style="list-style-type: none"> • Automatic calibration after turned on, • Optical - sound signaling, • Large, easy to read LCD graphic display with backlight, • ZOOM function - More precise location of small metal elements with visualization of their location | Socket access element included | Metal ends | | |
| Resolution | 3840 x 2160 - 8.3 Mpx 4K UHD , 3072 x 2048 - 6 Mpx , 3072 x 1728 - 5 Mpx , 2592 x 1620 - 4.6 Mpx , 2688 x 1520 - 4 Mpx , 2048 x 1536 - 3 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p | | | | | | | | |
| Lens | 2.8 mm | | | | | | | | |
| View angle | • 111° (manufacturer data) • 105° (our tests result) | | | | | | | | |
| White light LED illuminator range | 30 m | | | | | | | | |
| Range of IR illumination | 30 m | | | | | | | | |
| Image compression method | H.265+ / H.265 / H.264+ / H.264 / MJPEG | | | | | | | | |
| Main stream frame rate | 20 fps @ 8.3 Mpx 25 fps @ 4 Mpx | | | | | | | | |
| Memory card slot | Micro SD memory cards up to 256GB support (possible local recording) | | | | | | | | |
| RS-485 interface | -- | | | | | | | | |
| Alarm inputs / outputs | -- | | | | | | | | |
| Audio | <ul style="list-style-type: none"> • Microphone built-in • Audio transmission via network • Audio detection • Compliance with the AAC standard | | | | | | | | |
| Network interface | 10/100 Base-T (RJ-45) | | | | | | | | |
| Network protocols | IPv4/IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, IGMP, NFS, PPPoE, Bonjour | | | | | | | | |
| WEB Server | Built-in | | | | | | | | |
| Max. number of on-line users | 20 | | | | | | | | |
| ONVIF | 2.1.1.2 | | | | | | | | |
| Mobile phones support | Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS | | | | | | | | |
| Default IP address | 192.168.1.108 | | | | | | | | |
| Default admin user / password | admin / The administrator password should be set at the first start | | | | | | | | |
| Web browser access ports | 80, 37777 | | | | | | | | |
| PC client access ports | 37777 | | | | | | | | |
| Mobile client access ports | 37777 | | | | | | | | |
| Port ONVIF | 80 | | | | | | | | |

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

| | | | | | | | | | | | | | | | |
|-----------------------|--|--|-------------------|--|--|--|-----------------------------|--|-------------------|---------|-----------------|---------|---|-----------------|--|
| RTSP URL | rtsp://admin.hasko@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin.hasko@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream | | | | | | | | | | | | | | |
| Main features | <ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • NAS - Network Attached Storage support • Day/Night mode (color&w/auio) • ICR - Movable InfraRed filter • Auto White Balance • AGC - Automatic Gain Control • Possibility to change the resolution, quality and bit rate • Configurable Privacy Zones • video tampering • Mirror - Mirror image • Full Color - colorful night mode • Smart motion detection (with recognizing people and vehicles) • SMD PLUS - searching for an object classified as: human, motor vehicle • IVS analysis : intrusion, crossing the line (tripwire) - classification of people and vehicles | | | | | | | | | | | | | | |
| Housing | Dome - Metal + Plastic | | | | | | | | | | | | | | |
| Color | White | | Black | | Red | | Silver | | | | | | | | |
| "Index of Protection" | IP67 | | | | | | | | | | | | | | |
| Vandal-proof | -- | | | | | | | | | | | | | | |
| Power supply | <ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 420 mA | | | | Built-in 3.7V / 300mAh battery, charging via USB-C connector | | | | | | | | | | |
| Power consumption | <ul style="list-style-type: none"> • ≤ 5.9 W @ PoE • ≤ 5 W @ 12 VDC | | | | | | | | | | | | | | |
| Operation temp | 40 °C ... 60 °C | | | | | | | | | | | | | | |
| Weight | 0.46 kg | | 0.084 kg | | 1.15 kg | | 0.15 kg | | 0.043 kg | 0.21 kg | 0.255 kg | 0.16 kg | | | |
| Dimensions | Ø 122 x 99 mm | | 52 x 46.5 x 15 mm | | 112 x 112 x 50 mm | | 220 x 220 x (56 ... 230) mm | | 148 x 68 x 30 mm | | 45 x 45 x 37 mm | | <ul style="list-style-type: none"> • Ø 16 mm - Inner diameter, • Ø 20 mm - External diameter, • 400 mm - Length (CABLE PROTECTOR) • 480 mm - Total length | 63 x 65 x 36 mm | |
| Supported languages | Polish, English, Czech, French, Spanish, Dutch, German, Russian, Portuguese, Romanian, Turkish, Ukrainian, Hungarian, Italian | | | | | | | | | | | | | | |
| Manufacturer / Brand | DAHUA | | UNIVIEW | | | | UNI-T | | STASINSKI / JAVEL | | | | | | |
| Guarantee | 2 years | | 2 years | | 2 years | | 2 years | | 2 years | | 2 years | | | | |

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00