




	ROUTER AX18 Wi-Fi 6, 2.4 GHz, 5 GHz, 574 Mbps + 1201 Mbps DAHUA	HUB USB 3.0 H1208A	STEEL LINE CLAMP ZL-5
			
	48.69 EUR 48.69 EUR	5.17 EUR 5.17 EUR	0.16 EUR 0.16 EUR
Application	Steel lines Ø 5 mm
Material	Metal
Frequency range	2.4 GHz, 5 GHz ,
Connectors	...	<ul style="list-style-type: none"> • 1 x plug - USB-A • 4 x socket - USB-A 	...
Length of the cable	...	18 cm	...
USB standard	...	3.0	...
Antenna type	4 x Omnidirectional antenna 5 dBi - Integrated, 2x2 MU-MIMO
Standards	IEEE 802.11ax/n/b/g @ 2.4 GHz , IEEE 802.11ax/ac/n/a @ 5 GHz
Baud rates	574 Mbps + 1201 Mbps
LAN ports	1 x 10/100/1000 Mbps - WAN 3 x 10/100/1000 Mbps - LAN
LED indicators	Power
Receiver sensitivity	2.4 GHz : <ul style="list-style-type: none"> • 11n HT20 MCS0 : -95 dBm • 11n HT20 MCS7 : -75 dBm • 11n HT40 MCS0 : -92 dBm • 11n HT40 MCS7 : -72 dBm • 11ax HE20 MCS0 : -95 dBm • 11ax HE20 MCS11 : -65 dBm • 11ax HE40 MCS0 : -92 dBm • 11ax HE40 MCS11 : -62 dBm 5 GHz : <ul style="list-style-type: none"> • 11ac VHT80 MCS0 : -89 dBm • 11ac VHT80 MCS9 : -62 dBm • 11ax HE80 MCS0 : -89 dBm • 11ax HE80 MCS11 : -59 dBm

DDNS	✓
DHCP server	✓
Firmware update	✓
Protections	WPA/WPA2, WPA3
Management interface	Web browser ; WiLynk application
Operation modes	Router
Transmitter power	< 20 dBm ± 2 dBm
Power supply	12 V DC / 1 A (power adapter included)
Main features	<ul style="list-style-type: none"> • Wi-Fi 6 support - a standard that offers higher speeds, better performance in high-traffic environments • WPS/RESET button • The WPS function allows to easy establish an encrypted connection • Built-in 3-port switch • WAN : Fixed, or dynamic IP address, PPPoE • DHCP : DHCP server, DHCP client list, address reservation • Guest Network - a separate and secure network for guests • parental control • NAT : Port forwarding, Port Triggering, UPnP, DMZ • VPN networks: PPTP, L2TP, OpenVPN, WireGuard, IPSec, Zerotier • Access control • Remote management • VLAN • IPv6 compliance 	Solid workmanship	Corrosion resistance
Operation temp	0 °C ... 40 °C
Permissible relative humidity	10 % ... 90 % (non-condensing)
Weight	0.29 kg	0.03 kg	0.015 kg
Dimensions	252 x 155 x 178 mm	88 x 17 x 9 mm	25 x 25 x 15 mm
Manufacturer / Brand	DAHUA	UNITEK	...
Guarantee	2 years	2 years	2 years