




	<a href="#">EXTENDER USB-EX-200</a>	<a href="#">EXPANSION PLUG KW-8/5X80 KLIMAS</a>	<a href="#">EXTENDER HDMI-EX-70IR-4KV2</a>
			
	361.93 DKK 361.93 DKK	1.14 DKK 1.14 DKK	865.73 DKK 865.73 DKK
Connectors	<ul style="list-style-type: none"> <li>• USB</li> <li>• RJ45</li> </ul>	...	...
Material	...	<ul style="list-style-type: none"> <li>• Expansion plug, Polypropylene</li> <li>• Screw, Steel galvanized</li> </ul>	...
Drilling diameter	...	8 mm	...
Expansion plug length	...	50 mm	...
Range	<ul style="list-style-type: none"> <li>• 50 m - USB 2.0,</li> <li>• 100 m - USB 1.1</li> </ul>	...	...
Screw dimensions	...	Ø 5 x 80 mm, PZ-2	...
UTP category	5e / 6	...	...
Application	...	<ul style="list-style-type: none"> <li>• Concrete</li> <li>• Solid clay brick</li> <li>• Solid sand-lime brick</li> </ul>	...
Manufacturer / Brand	...	KLIMAS	...
Supported HDMI resolutions	...	...	720p, 1080i, 1080p, 800 x 600, 1280 x 960, 1280 x 800, 1280x768, 1680x1050, 1360 x 768, 1366 x 768, 1600 x 900, 1024 x 768 3840 x 2160 - 4K UHD, max. 4096 x 2160
Maximal transmission range	...	...	<ul style="list-style-type: none"> <li>• 70 m @ UTP cat. 6 / 6A / 7 @ 4K UHD</li> <li>• 50 m @ UTP cat. 5e @ 4K UHD</li> </ul>
Supported audio formats	...	...	LPCM, DTS-HD, DTS-Audio, Dolby Digital 5.1CH, Dolby Atmos
Supported HDMI standard	...	...	2.0
HDCP	...	...	2.2

Main features	...	...	<ul style="list-style-type: none"> <li>• IR receiver / IR transmitter - External</li> <li>• Very good image quality with no visible distortions caused by compression</li> <li>• No delays in video transmission</li> <li>• Built-in HDMI signal splitter in the transmitter</li> <li>• Built-in ESD protection</li> <li>• EDID support</li> <li>• HDR10 support</li> </ul>
Power supply	...	...	5 V DC / 2 A - Transmitter (power adapter included)
Power consumption	...	...	8 W (total)
Operation temp	...	...	-20 °C ... 60 °C
Permissible relative humidity	...	...	0 % ... 90 % (non-condensing)
Weight	0.05 kg (total)	...	0.14 kg
Dimensions	61 x 30 x 20 mm	...	85 x 75.5 x 16.5 mm - Transmitter or receiver dimensions
Guarantee	2 years	2 years	2 years