



	IP CAMERA BCS-L-PIP12FW PINHOLE - 1080p 2.8 mm BCS Line	MONITORS DESK MOUNT MC-691 MACLEAN
		
	287.46 EUR 287.46 EUR	61.05 EUR 61.05 EUR
Standard	IP	...
Mounting standard	...	VESA 75, VESA 100
Screen size range	...	13 " ... 27 "
Bearing capacity	...	8 kg
Resolution	1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p	...
Tilt adjustment	...	-45 ° ... 45 °
Horizontal rotation	...	180 °
Sensor	1/3 " Progressive Scan CMOS	...
Rotation in the plane of the screen	...	360 °
Mount tube diameter	...	Ø 35 mm
Lens	2.8 mm @ F2.0 (pinhole)	...
View angle	96 °	...
Range of IR illumination	—	...
Memory card slot	—	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	—	...
Audio	<ul style="list-style-type: none"> • Audio input • Microphone built-in, • Audio output • Bi-directional audio streaming support 	...
Main stream frame rate	25 fps @ 1080p	...
Interface	10/100 Base-T (RJ-45)	...
WEB Server	Built-in	...
Max. number of on-line users	20	...
ONVIF	✓	...
Intelligent image analysis	<ul style="list-style-type: none"> • intrusion • crossing the line (tripwire) 	...

Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Configurable Privacy Zones • Motion Detection • AWB - Auto White Balance • AGC - Automatic Gain Control • AES - Auto Electronic Shutter • Day/night mode • ICR - Movable InfraRed filter • Mirror - Mirror image • D-ZOOM - Digital Zoom : 16 x 	...
Mobile phones support	<ul style="list-style-type: none"> Port no.: 37777 or access by a cloud (P2P) • Android: Free application BCS Manager • iOS (iPhone): Free application BCS Manager 	...
Default IP address	192.168.1.108	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80, 37777	...
PC client access ports	37777	...
Mobile client access ports	37777	...
Port ONVIF	80	...
RTSP URL	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
Power supply	12 V DC / 130 mA	...
Power consumption	max. 1.56 W	...
Housing	Mini - Metal	...
Color	Black	Black
"Index of Protection"	—	...
Mechanical protection class	—	...
Operation temp	-40 °C ... 60 °C	...
Weight	0.08 kg	6 kg
Dimensions	<ul style="list-style-type: none"> • 44 x 35 x 30 mm • 50 cm (cable length) 	1330 x 550 x 83 mm
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Romanian, Turkish, Ukrainian, Hungarian, Vietnamese, Italian	...
Manufacturer / Brand	BCS Line	MACLEAN
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00