



	INSULATION STRIPPER STRF/KLUCZ	ACCESS CONTROLLER ASI3213G-MW DAHUA
		
	10.33 USD 10.33 USD	535.51 USD 535.51 USD
Material	PET	...
Sensor	...	CMOS
Matrix size	...	2 Mpx
Application	Coaxial cable RG6 Coaxial cable RG59	...
Resolution	...	1920 x 1080 - 1080p
Standard	...	TCP/IP
IR illuminator	...	✓
LED illuminator	...	✓
Temperature measurement	...	—
Temperature measurement range	...	—
Accuracy of temperature measurement	...	—
Face recognition distance	...	0.3 m ... 1.5 m (max 1500 faces in the database)
RFID proximity reader built-in	...	<ul style="list-style-type: none"> • 13.56 MHz S50 • Memory of 1500 RFID cards
Internal memory	...	Support storage of 150 000 records
Video output	...	—
RS-485 interface	...	✓
RS-232 interface	...	—
Wiegand interface	...	—
USB	...	1 x USB 2.0
Memory card slot	...	—
Alarm inputs / outputs	...	1 / 1 - Relay outputs
Audio	...	Voice message
Network interface	...	1 x 10/100 Base-T (RJ-45)
Network protocols	...	IPv4, RTSP, RTP, TCP, UDP, P2P
WEB Server	...	Built-in
ONVIF	...	—
Default IP address	...	192.168.1.108

Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80, 37777
PC client access ports	...	37777
Main features	...	<ul style="list-style-type: none"> • Built-in LCD display showing the image from the video camera - 4.3 " capacitive touch screen, 480 x 272 px • Identification modes : PIN, Proximity identifier 13.56 MHz S50, Face recognition, Any combination of the above • 1500 users • Software update via network • Real-time Surveillance • Multiple Authentication • Take face image after swiping card • Auto-Registration • Backup to USB drive (pendrive, external drive) • Output button support • Door status detection • Lock control • Function to prevent of multiple use of the same code/card to gain access (anti-passback) • Auto-uploads alarm messages to Master or client station after entering the duress code to open the door • Ability to work with reed switch and signalling the door being opened too long • 128 General Purpose Schedules • Unlocking the transition only when more than one user is present • Tamper protections
Power supply	...	12 V DC / 1.5 A (power adapter included)
Power consumption	...	≤ 18 W
Housing	...	Plastic (ABS)

Color	...	Black + Silver
"Index of Protection"	...	—
Operation temp	...	-10 °C ... 55 °C
Weight	...	<ul style="list-style-type: none"> • 0.22 kg (without stand) • 0.24 kg (with stand)
Dimensions	...	<ul style="list-style-type: none"> • 116 x 107 x 22 mm (without stand) • 116 x 107 x 78 mm (with stand)
Supported languages	...	English
Manufacturer / Brand	...	DAHUA
Guarantee	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00