



	ETHERNET + EPOE CONVERTER LR1002 DAHUA	SET OF UTP / 2-WIRE CONVERTERS FOR LAN+POE TRANSMISSION ETH-2WIRE-SET 2 PCS SET ATTE
		
	4476.19 HUF 4476.19 HUF	44666.67 HUF 44666.67 HUF
In package	2 pcs The price for package	...
Transmission ports	1 pcs BNC	...
Connectors	...	<ul style="list-style-type: none"> • 1 pcs RJ45 • 1 pcs terminals (screw terminals) - 0.32 ... 3.3 mm² (22 ... 12 AWG)
LAN ports	1 pcs RJ45	1 pcs RJ45 100 Mbps
Terminals	...	<p>ETH-2WIRE-TX :</p> <ul style="list-style-type: none"> • PoE IN - Passive PoE ≤ 30 W, PoE (802.3at) ≤ 30 W, PoE (802.3af) ≤ 15 W ("+" : 1, 2 pins; "+/-" : 3, 6 pins) or ("+" : 4, 5 pins; "+/-" : 7, 8 pins) • Power • DATA - 2-wire <p>ETH-2WIRE-RX :</p> <ul style="list-style-type: none"> • PoE OUT - Passive PoE ("+" : 4, 5 pins; "-" : 7, 8 pins) • Power • DATA - 2-wire
Transmission speed	10 / 100 Mbps Full Duplex	100 Mbps
Transmission range	max. 1000 m @ 10 Mbps max. 400 m @ 100 Mbps The range of data transfer and power supply is strongly dependent on the cable used and the power required to supply the receiver	<ul style="list-style-type: none"> • 300 m @ 2-wire : UTP, • 100 m @ 2-wire : OMY-2X0.75 • 100 m @ UTP : Switch PoE - ETH-2WIRE-TX • 100 m @ UTP : ETH-2WIRE-RX - IP Camera
LED indicators	...	<ul style="list-style-type: none"> • Power • LAN • 2-wire
Protections	Overvoltage	<ul style="list-style-type: none"> • Overvoltage - LAN, DATA • Protection against reverse polarity connection - Power • Overload 0.6 A - PoE IN ETH-2WIRE-TX

Main features	<ul style="list-style-type: none"> • Plug & Play • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Support for IP cameras and network devices • Easy installation - doesn't require any configuration of IP nor MAC address • 2 pcs included 	<ul style="list-style-type: none"> • Plug & Play • Support for IP cameras and network devices • Full transparency for networks • Operation modes - Set with jumpers
Power supply	ePoE	ETH-2WIRE-TX : <ul style="list-style-type: none"> • 44 ... 56 V DC - PoE • 24 ... 56 V DC - Power ETH-2WIRE-RX : <ul style="list-style-type: none"> • 24 ... 56 V - Power • The output PoE voltage is equal to the input voltage
Power consumption	...	1.35 W (total)
Housing	...	Plastic (PC)
"Index of Protection"	...	IP20
Operation temp	...	-25 °C ... 65 °C
Weight	0.030 kg	0.03 kg (single element)
Dimensions	<ul style="list-style-type: none"> • 56 x 27 x 21 mm • 7 cm (cable length) 	51 x 51 x 24 mm (single element)
Manufacturer / Brand	DAHUA	ATTE
Guarantee	3 years	3 years