



	SWITCH POE IP-8-20-L2 8-PORT ATTE	SWITCH POE IPB-5-10A-S4 5-PORT ATTE
		
	362.69 CAD 362.69 CAD	115.39 CAD 115.39 CAD
LAN ports	<ul style="list-style-type: none"> • 2 x RJ45 10/100/1000 Base-TX - Uplink, • 8 x RJ45 10/100 Base-TX + PoE (802.3af/at) / Passive PoE 	<ul style="list-style-type: none"> • 1 x RJ45 10/100 Base-T - Uplink • 5 x RJ45 10/100 Base-T - PoE (802.3af/at) / Passive PoE
Management	—	—
LED diodes	Power, LAN	Power, LAN
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 Mbps : 8 LAN & PoE ports, • 10 / 100 / 1000 Mbps : 2 LAN ports 	10 / 100 Mbps : 1 Port LAN + 5 LAN & PoE ports
Maximal output power	<ul style="list-style-type: none"> • 40 W @ Passive PoE - 1 ... 8 ports, • 30 W @ PoE (802.3at) - 1 ... 8 ports, • 15.4 W @ PoE (802.3af) - 1 ... 8 ports 	<ul style="list-style-type: none"> • 40 W @ Passive PoE - 1 ... 5 ports, • 30 W @ PoE (802.3at) - 1 ... 5 ports • 15.4 W @ PoE (802.3af) - 1 ... 5 ports
Maximal total power	96 W	90 W

Main features	<ul style="list-style-type: none"> • Supported PoE devices: 802.3af/at, Passive PoE • Possibility to connecting in cascade @ 90 W • Built-in switching power supply : 48 V DC / 96 W • Efficiency : 92 % • PSU thermal protection • Short-circuit protection • Overload protection • The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 8 ports • Electronic fuse independently for each PoE channel • The modular design streamlines service tasks and enables quick and easy system expansion • The raster system of module assembly facilitates the expansion of the device by further modules • The ABOX-L2 mounting enclosure is equipped with 11 cable entries with glands in the 10 x M16 + 1 x M20 arrangement • "Index of Protection" : IP56 	<ul style="list-style-type: none"> • Supported PoE devices: 802.3af/at, Passive PoE • Possibility to connecting in cascade • Efficiency : 93 % @ 90 W • 5 polymer fuses - PoE • Possibility to power other devices powered from 55 V (screw connection) • PSU thermal protection • Short-circuit protection • Overload protection • The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 4 ports • Switch has built-in a 55 V DC power supply adapter with power of 90 W • "Index of Protection" : IP55
Power supply	• 190 ... 260 V AC - Built-in APS-90-480-OF switching mode power supply	180 ... 240 V AC - Built-in switching power supply
Weight	1.04 kg	0.43 kg
Dimensions	248 x 198 x 96 mm	158 x 118 x 77 mm
Manufacturer / Brand	ATTE	ATTE
Guarantee	3 years	3 years