



	RFID PROXIMITY CARD ATLO-307 13.56 MHz S50	ACCESS POINT 4G LTE +ROUTER ALINK-MR920 2.4 GHz 300 Mbps
		
	2.01 PLN 2.01 PLN	201.60 PLN 201.60 PLN
Standard	13.56 MHz S50	...
Frequency range	...	2.4 GHz
Compatibility	ISO/IEC 14443A	...
Possibility of programming the serial number (ID)	—	...
Ability to write to internal memory	1 kB	...
Serial Number overprint	—	...
Antenna type	...	2 x Omnidirectional antenna Wi-Fi - 8 dBi, 4G LTE
Standards	...	IEEE 802.11 b/g/n, 4G LTE, 3G
Baud rates	...	11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 150 / 50 Mbps
LAN ports	...	• 1 x 10/100 Mbps - LAN/WAN • 2 x 10/100 Mbps - LAN
Receiver sensitivity	...	• 11g 54M : -74 dBm • 11n HT20 MCS7 : -71 dBm • 11n HT40 MCS7 : -67 dBm
Transmitter power	...	< 27 dBm @ 2.4 GHz
LED indicators	...	Power, WAN, WLAN, LAN, GSM
Network type	...	• 4G : FDD-LTE B1/B3/B7/B8/B20/B28 - 2100 / 1800 / 2600 / 900 / 800 / 700 MHz • 4G : TDD-LTE B38/B40/B41 - 2600 / 2300 / 2500 MHz • 3G : DC- HSPA+/HSPA/UMTS B1/B8 - 2100 / 900 MHz
LTE	...	✓
QSS	...	—
WDS	...	—
DHCP server	...	✓

Protections	...	<ul style="list-style-type: none"> • WPA-PSK/WPA2-PSK • SSID hiding • MAC addresses filtering
Management interface	...	Web browser
Main features	Range : ~ 10 cm ,	<ul style="list-style-type: none"> • SIM socket • ON/OFF button • WPS/RESET button • DHCP client/server support • DHCP client list • Static routing • Default address : 192.168.1.1 • WAN Connection Backup - thanks to the fully functional WAN / LAN port, you can use various types of backup connections, including cable, fiber and DSL modems
Power supply	...	<ul style="list-style-type: none"> • 12 V DC / 1 A (power adapter included) • 5 V / 2 A via micro USB port
Operation temp	...	0 °C ... 40 °C
Permissible relative humidity	...	10 % ... 90 % (non-condensing)
Weight	0.005 kg	0.32 kg
Dimensions	86 x 54 x 0.8 mm	200 x 145 x 49 mm
Manufacturer / Brand	ATLO	ALINK
Guarantee	2 years	2 years