



	SWITCH POE CS4006-4GT-60 4-PORT DAHUA	CAMERA BRACKET DS-1602ZJ Hikvision
		
	1043.23 DKK 1043.23 DKK	278.67 DKK 278.67 DKK
Suitable for cameras	...	Hikvision
Material	...	Aluminum
Color	...	White
SAP Code	...	302700684
LAN ports	<ul style="list-style-type: none"> • 4 x RJ45 10/100/1000 Base-T (1 x Hi-PoE + 3 x PoE (802.3af/at)), • 2 x RJ45 10/100/1000 Base-T - Uplink 	...
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps : 4 LAN & PoE ports, • 10 / 100 / 1000 Mbps : 2 Uplink ports 	...
Maximal output power	<ul style="list-style-type: none"> • 60 W / port Hi-PoE - Port 1 • 30 W / port PoE 802.3af/at - 2 ... 4 ports 	...
Maximal total power	60 W	...
MAC addresses table	8k	...
Management	✓	...
Operation modes	Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6	...
LED diodes	Power, System, PoE, Link/Act	...

Main features	<ul style="list-style-type: none"> • Switch is managed through the web and the cloud (DoLynk Care application) • PoE power mode : The device supports 8-pin power supply - wires : 1-2(+), 3-6(-), 4-5(+), 7-8(-) • Intelligent management of Power Supply Unit power's output stage • protection against lightning discharges and voltage differences and strokes between devices • Watchdog PoE • Loop Protection • Compliance with the LLDP protocol • Port Based VLAN : 32 • Data Flow Control (802.3x) • DHCP client • RESET button • Kensington Lock • Possibility to mount to the wall 	...
Certificates	CE	...
Protections	<ul style="list-style-type: none"> • Protection against lightning discharges (common/differential) : 4 / 2 kV • Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV 	...
Housing	Desktop, Metal	...
Power supply	53 V DC / 1.22 A (power adapter included)	...
Power consumption	max. 65 W	...
Operation temp	-10 °C ... 55 °C	...
Weight	0.3 kg	1.15 kg
Dimensions	130 x 90 x 26 mm	312 x 180 x 98 mm
Manufacturer / Brand	DAHUA	Hikvision
Guarantee	3 years	2 years