



	<a href="#">ACCESS CONTROLLER WITH TEMPERATURE MEASUREMENT APTI-AI70FRTD-V2 4.5 mm - 1080p</a>	<a href="#">TV OR MONITOR MOUNT BRATECK-PLB-CE344</a>
		
	60.03 EUR 60.03 EUR	23.65 EUR 23.65 EUR
Scanning system	Progressive	...
Optical zoom	—	...
Mounting standard	...	VESA 75, 100, 200, 200x100, 400, 400x200
Screen size range	...	32 " ... 55 "
Bearing capacity	...	50 kg
Sensor	1/2.8 " SONY Starvis™ Back-illuminated CMOS 1/5 " GC2145	...
Matrix size	2.1 Mpx 2 Mpx	...
Pixel pitch	1.75 μm	...
Lens	4.5 mm 2.4 mm	...
View angle	68 ° 70 °	...
Distance from mounting surface	...	(manufacturer data) : 1050 ... 1560 mm from ceiling Our tests results : 920 ... 1510 mm from ceiling
Resolution	1920 x 1080 - 1080p 800 x 600 - 0.48 Mpx	...
Tilt adjustment	...	-15 ° ... 15 °
Standard	TCP/IP	...
Horizontal rotation	...	360 °
Range of IR illumination	5 m	...
Rotation in the plane of the screen	...	—
White light LED illuminator range	5 m	...
Temperature measurement	✓	...
Temperature measurement range	35 °C ... 42 °C	...

Accuracy of temperature measurement	± 0.3 °C	...
Face recognition distance	0.5 m ... 1.5 m (max 30 000 faces in the database)	...
Temperature measurement distance	0.5 m ... 1.3 m optimal distance : 0.75 m	...
Internal memory	Support storage of 25 000 records	...
Video output	—	...
RS-485 interface	✓	...
Wiegand interface	✓	...
Memory card slot	—	...
Alarm inputs / outputs	0 / 2 ( bolt control, signaling of exceeding the temperature )	...
Audio	Speaker built-in	...
Network interface	10/100 Base-T (RJ-45)	...
Network protocols	IPv4, HTTP, HTTPS, TCP/IP	...
WEB Server	Built-in	...
Max. number of on-line users	20	...
ONVIF	—	...
RS-485	✓	...
Default IP address	DHCP / 192.168.1.88	...
Default admin user / password	admin / 12345	...
Web browser access ports	7080	...
PC client access ports	7080	...
Main features	<ul style="list-style-type: none"> <li>• Built-in LCD display showing the image from the video camera and the result of temperature measurement - 1024 x 600 px</li> <li>• Wiegand 26</li> <li>• Day/Night mode (color/b&amp;w/auto)</li> <li>• RESET button</li> <li>• Relay output operating modes: access control or notification of an exception</li> </ul>	...
Power supply	12 V DC	...
Power consumption	≤ 12 W	...
Housing	Compact - Metal	...
Color	Silver	Black
"Index of Protection"	IP66	...

Operation temp	15 °C ... 25 °C - temperature measurement only in closed rooms (stabilized temperature)	...
Weight	0.94 kg	5.7 kg
Dimensions	305 x 112 x 59 mm	1080 x 520 x 60 mm
Montage hole diameter	33 mm	...
Length of the cable	64 cm	...
Supported languages	Polish, English, French, Spanish, German, Portuguese, Russian, Turkish, Italian	...
Manufacturer / Brand	APTI	...
Guarantee	3 years	2 years