



	ROUTER RG-EG210G-P 8 PoE REYEE	ACCESS POINT 4G LTE +ROUTER CUDY-LT400 2.4 GHz, 5 GHz, 300 Mbps
		
	236.76 EUR 236.76 EUR	65.32 EUR 65.32 EUR
Frequency range	...	<ul style="list-style-type: none"> • Wi-Fi : 2.4 GHz, 5 GHz, • LTE : 2600 MHz, 2100 MHz, 1800 MHz, 900 MHz, 800 MHz
WAN interface	<ul style="list-style-type: none"> • 1 x WAN 10/100/1000 Mbps (RJ-45) 	...
Antenna type	...	<ul style="list-style-type: none"> • 2 x Omnidirectional antenna Wi-Fi • 2 x Omnidirectional antenna 4G LTE
Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, 802.3z, IEEE 802.3af, IEEE 802.3at	IEEE 802.11 b/g/n
Port USB	—	...
Baud rates	...	<ul style="list-style-type: none"> • Wi-Fi : 300 Mbps • LTE : 150 Mbps / 50 Mbps
Power supply PoE	Power output - LAN ports : PoE (802.3af/at) max. 70 W (total)	...
LAN ports	<ul style="list-style-type: none"> • 8 x LAN & PoE 10/100/1000 Mbps (RJ-45) • 1 x LAN/WAN 10/100/1000 Mbps (RJ-45) 	1 x 10/100 Mbps - Uplink / LAN 3 x 10/100 Mbps - LAN
Mobile phones support	Android: Free application Ruijie Reyee iOS (iPhone): Free application Ruijie Reyee	...
LED indicators	Status, Link/Act	Power, INTERNET, LAN/WAN, LAN 1, LAN 2, LAN 3, WiFi, 4G
SIM socket	...	1 x mini SIM
DDNS	✓	✓
DHCP server	✓	✓
Firmware update	✓	✓

Protections	<ul style="list-style-type: none"> • ACL • IP-MAC Binding • MAC addresses filtering • Support for dynamic ARP mapping and static table • NAT / NAPT • Port Mapping 	DoS attacks protection, SPI network firewall, domain filtering, IP and MAC filtering, IP and MAC binding
Management interface	<ul style="list-style-type: none"> • Ruijie Cloud Central Management System • Configuration using the Ruijie Reeye application • Remote management • Web browser 	Web browser
Power supply	100 ... 240 V AC, 50 / 60 Hz	12 V DC / 2.5 A (power adapter included)
Power consumption	≤ 80 W (at full load)	...
Main features	<ul style="list-style-type: none"> • VPN networks: IPsec VPN, Open VPN, L2TP VPN, PPTP VPN, etc. • Static / dynamic routing • WAN : PPPoE, PPTP, L2TP • DHCP client/server support • Access Control List - ACL package filtering based on source and destination IP addresses • Rate limit • Load balance • NAT • Reboot schedule • View topology and network status • RESET button 	<ul style="list-style-type: none"> • Internet access filtering • Static / dynamic routing • Built-in 4-port switch • Wireless transmission statistics • QoS • Rate limit • Access control • Remote management • DMZ • parental control • Guest Network - a separate and secure network for guests
Operation temp	0 °C ... 40 °C	0 °C ... 45 °C
Permissible relative humidity	10 % ... 90 % (non-condensing)	5 % ... 95 % (non-condensing)
Weight	0.53 kg	0.264 kg
Dimensions	207 x 109 x 27 mm	229 x 147 x 32 mm
Manufacturer / Brand	RUIJIE / REYEE	CUDY
Guarantee	2 years	2 years