




	ACCESS CONTROLLER WITH FACE RECOGNITION + READER ATLO-FR-601	CRIMPING TOOL ZTA-A	SMART GATE AND DOOR CONTROLLER GATEBOX-PRO/BLEBOX Wi-Fi, 12 ... 24 V DC/AC
			
	48.27 EUR 48.27 EUR	19.62 EUR 19.62 EUR	62.92 EUR 62.92 EUR
Material	...	Metal / PET	...
Rated voltage	12 ... 24 V DC/AC
Face recognition distance	0.5 m ... 1 m (max 1000 faces in the database)
Maximal total load	—
Total maximal current	20 mA / Control output
RFID proximity reader built-in	Unique EM 125kHz - Number of supported proximity cards : 10 000
Number of inputs	2
Fingerprint reader built-in	Memory of 600 fingerprint patterns
Number of outputs	2
Range of IR illumination	5 m
Connector type	screw terminals
White light LED illuminator range	—
Video output	—
Application	...	Crimping ferrules : • Single ferrules - 0.25 ... 10 mm ² , • Double ferrules - 2 x 0.25 ... 2 x 4 mm ²	swing gates, sliding gates, garage gates, doors
Wiegand interface	✓
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11g
RS-485 interface	—
Mobile phones support	• The wBox free application on Android • The wBox free application on iOS
Alarm inputs / outputs	0 / 1 - Relay output

Main features	<ul style="list-style-type: none"> • Built-in LCD display showing the image from the video camera • Identification modes : Face recognition, Fingerprint, Proximity identifier Unique EM 125kHz, Any combination of the above • Wiegand 26 • LEDs and buzzer • Buzzer for acoustic signaling of some system events
Power supply	12 V DC
Power consumption	<ul style="list-style-type: none"> ≤ 3.6 W (operation) ≤ 2.2 W (standby)
Main features	...	High durability tool, made from high quality materials	<ul style="list-style-type: none"> • Control of the electric strike and automatic gate, • Multiple users support from anywhere, • Control many objects from one app, • remote access, • voice control, • Omnidirectional antenna Wi-Fi 5 dB, • SMA-RP socket • µWiFi technology support
Housing	Aluminum + Tempered glass, Vandal-proof	...	Plastic, Waterproof, Weatherproof
"Index of Protection"	IP65	...	IP54
Color	Silver + Black	...	Black
Operation temp	-40 °C ... 60 °C
Operation temp	-20 °C ... 50 °C
Weight	0.38 kg	0.4 kg	0.1 kg
Dimensions	170 x 70 x 24 mm	173 x 76 x 21 mm	<ul style="list-style-type: none"> • 92 x 50 x 28 mm - without antenna • 230 x 85 x 28 mm - with antenna, vertical • 197 mm - Antenna
Manufacturer / Brand	ATLO	...	BleBox
Guarantee	2 years	2 years	2 years