

	IP CAMERA IPC-HFW1239TL1-A-IL Smart Dual Light - 1080p 2.8 mm DAHUA	CONNECTOR STRIP KE-ZPT4-35.0 SIMET	HEX HEAD SCREW SS-M8X50/KL-8.8	HEX HEAD SCREW SS-M8X30/KL-8.8	ROUTER WIFI RG-EG105GW-X Wi-Fi 6, 574 Mbps + 2404 Mbps REYEE
					
	49904.76 HUF 49904.76 HUF	2734.29 HUF 2734.29 HUF	74.29 HUF 74.29 HUF	66.67 HUF 66.67 HUF	92952.38 HUF 92952.38 HUF
Number of terminal pairs	...	4	...	...	...
Standard	TCP/IP	...	...	...	...
Size	...	...	M8	M8	...
Frequency range	...	...	...	...	2.4 GHz, 5 GHz
Connector type	...	terminals	...	...	...
Material	...	...	Steel galvanized	Steel galvanized	...
Strength class	...	...	8.8	8.8	...
Nominal voltage	...	500 V	...	...	...
Sensor	1/2.8 " Progressive Scan CMOS	...	...	...	...
Matrix size	2.1 Mpx	...	...	...	...
Wire gauge	...	16 ... 35 mm <sup>2</sup>	...	...	...
Wrench size	...	...	13 mm	13 mm	...
Dielectric	...	Plastic	...	...	...
Thread length	...	...	50 mm	30 mm	...
Antenna type	...	...	...	...	2x2 MIMO - built-in • 5 dBi @ 2.4 GHz • 5 dBi @ 5 GHz
Resolution	1920 x 1080 - 1080p, 1280 x 960 - 1.3 Mpx, 1280 x 720 - 720p	...	...	...	...
Lens	2.8 mm	...	...	...	...
Standards	...	...	...	...	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, 802.3z, IEEE 802.11 a/b/g/n/ac/ax, Wi-Fi 6
View angle	104 °	...	...	...	...
Range of IR illumination	30 m	...	...	...	...
Baud rates	...	...	...	...	574 Mbps @ 2.4 GHz + 2404 Mbps @ 5 GHz
White light LED illuminator range	30 m	...	...	...	...
S/N ratio	> 56 dB	...	...	...	...
Memory card slot	—	...	...	...	...
LAN ports	...	...	...	...	• 1 x LAN 10/100/1000 Mbps (RJ-45) • 3 x LAN/WAN 10/100/1000 Mbps (RJ-45)
WAN interface	...	...	...	...	1 x WAN x 10/100/1000 Mbps (RJ-45)
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...	...	...	...
Alarm inputs / outputs	—	...	...	...	...
LED indicators	...	...	...	...	Status, Link/Act, Mesh
DDNS	...	...	...	...	✓
DHCP server	...	...	...	...	✓
Audio	• Microphone built-in • Audio output • Audio detection • Compliance with the AAC standard	...	...	...	...
Port USB	...	...	...	...	✓
Firmware update	...	...	...	...	✓
Main stream frame rate	25 fps @ 1080p	...	...	...	...
Power supply PoE	...	...	...	...	—
Network interface	10/100 Base-T (RJ-45)	...	...	...	...
WEB Server	Built-in	...	...	...	...
Max. number of on-line users	6	...	...	...	...
ONVIF	✓	...	...	...	...
Protections	...	...	...	...	• TCP scan blocking • ACL • IP-MAC Binding • MAC addresses filtering • Support for dynamic ARP mapping and static table • NAT / NAPT • Port Mapping • Mechanisms to prevent the most common types of DoS (Denial-of-Service) attacks
Default IP address	192.168.1.108	...	...	...	...
Default admin user / password	admin / - The administrator password should be set at the first start	...	...	...	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Web browser access ports	80, 37777	...	...	...	...
Management interface	...	...	...	...	<ul style="list-style-type: none"> <li>• Ruijie Cloud Central Management System</li> <li>• Configuration using the Ruijie Reyeec application</li> <li>• Remote management</li> <li>• Web browser</li> </ul>
PC client access ports	37777	...	...	...	...
Mobile client access ports	37777	...	...	...	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">DMSS</a></li> <li>• iOS (iPhone): Free application <a href="#">DMSS</a></li> </ul>	...	...	...	<ul style="list-style-type: none"> <li>Android: Free application <a href="#">Ruijie Reyeec</a></li> <li>iOS (iPhone): Free application <a href="#">Ruijie Reyeec</a></li> </ul>
Port ONVIF	80	...	...	...	...
RTSP URL	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...	...	...	...
Main features	...	...	DIN 933 compliance	DIN 933 compliance	<ul style="list-style-type: none"> <li>• Support for Reyeec Mesh technology</li> <li>• VPN networks: IPsec VPN, Open VPN, L2TP VPN, PPTP VPN, etc.</li> <li>• Static / dynamic routing</li> <li>• WAN : PPoE, PPTP, L2TP support</li> <li>• DHCP client/server support</li> <li>• Access Control List - ACL package filtering based on source and destination IP addresses</li> <li>• Rate limit</li> <li>• Load balance</li> <li>• NAT</li> <li>• Reboot schedule</li> <li>• View topology and network status</li> <li>• RESET button</li> </ul>
Main features	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Image rotation and mirror</li> <li>• Motion Detection - max. 4 configurable zones</li> <li>• Privacy zones - max. 4</li> <li>• Intelligent image analysis : Human detection</li> </ul>	...	...	...	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 530 mA</li> </ul>	...	...	...	100 ... 240 V AC, 50 / 60 Hz
Operation temp	...	...	...	...	0 °C ... 40 °C
Permissible relative humidity	...	...	...	...	10 % ... 90 % (non-condensing)
Power consumption	<ul style="list-style-type: none"> <li>• ≤ 6.3 W @ 12 V DC</li> <li>• ≤ 7.8 W @ PoE</li> </ul>	...	...	...	≤ 20 W
Housing	Compact - Metal	...	...	...	...
Color	White + Black	Black	...	...	...
"Index of Protection"	IP67	...	...	...	...
Vandal-proof	—	...	...	...	...
Operation temp	-40 °C ... 60 °C	...	...	...	...
Weight	0.31 kg	...	0.021 kg	0.015 kg	1.1 kg
Dimensions	198 x 80 x 76 mm	115 x 58 x 31 mm	...	...	315 x 188 x 188 mm
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Russian, Portuguese, Romanian, Turkish, Ukrainian, Hungarian, Italian	...	...	...	...
Manufacturer / Brand	DAHUA	SIMET	...	...	RUIJIE / REYEE
Guarantee	3 years	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00