





	<a href="#">CABLE USB-WG/1.5M 1.5 m</a>	<a href="#">OMNIDIRECTIONAL ANTENNA AMO-2G10 2.35 GHz ... 2.55 GHz 10 dBi UBIQUITI</a>	<a href="#">INSULATION STRIPPER HT-332</a>	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HDW2241M-E2-0280B - 1080p 2.8 mm DAHUA</a>
				
	0.74 GBP 0.74 GBP	181.92 GBP 181.92 GBP	2.62 GBP 2.62 GBP	172.03 GBP 172.03 GBP
Material	...	...	PET	...
Frequency range	...	2.35 GHz ... 2.55 GHz	...	...
Gain	...	10 dBi	...	...
Wave polarization	...	dual linear	...	...
Standard	...	...	...	HD-CVI, HD-TVI, AHD, PAL
VSWR	...	1.7	...	...
Cable	USB - A Plug / USB - A Socket	...	...	...
Horizontal beam width (H)	...	360 °	...	...
Sensor	...	...	...	2 x 1/2.8 " Progressive Scan CMOS
Application	...	...	Coaxial cable RG58 RG59 RG6	...
Length of the cable	1.5 m	...	...	...
Vertical beam width (V)	...	12 °	...	...
USB standard	2.0	...	...	...
Connector	...	2 x SMA-RP	...	...
Matrix size	...	...	...	2 x 2.1 Mpx
Mast mounting diameter	...	max. Ø 85 mm	...	...
Length of the cable	...	—	...	...
Main features	<ul style="list-style-type: none"> <li>• Solid workmanship</li> <li>• Very flexible</li> </ul>	High resistance to wind and weather	Left shield width adjustment	...
Resolution	...	...	...	1920 x 1080 - 1080p , 1280 x 720 - 720p , 960 x 576 - 960H, PAL for single camera
Range of IR illumination	...	...	...	30 m - for single camera
IR illuminator power adjustment	...	...	...	Automatic
Lens	...	...	...	2.8 mm
View angle	...	...	...	<ul style="list-style-type: none"> <li>• 110 ° (manufacturer data)</li> <li>- for single camera</li> <li>• 106 ° (our tests result)</li> </ul>
IR illuminator support	...	...	...	ICR - Movable InfraRed filter
S/N ratio	...	...	...	> 65 dB
Video output	...	...	...	2 x : HD-CVI / HD-TVI / AHD / PAL, 1 Vpp / 75 Ω
Audio	...	...	...	External microphone input - HD-CVI only

Main features	...	...	...	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• ICR - Movable InfraRed filter</li> <li>• Auto White Balance</li> <li>• AGC - Automatic Gain Control</li> <li>• Sharpness - sharper image outlines</li> </ul>
OSD menu	...	...	...	OSD menu available via DAHUA recorder
Power supply	...	...	...	12 V DC / 760 mA
Power consumption	...	...	...	≤ 9.2 W
Housing	...	...	...	Dome, Aluminum
Color	...	...	...	White
Vandal-proof	...	...	...	—
"Index of Protection"	...	...	...	IP67
Operation temp	...	...	...	-40 °C ... 60 °C
Weight	0.045 kg	2.19 kg	...	0.77 kg
Dimensions	...	1010 x 122 x 105 mm	...	201 x 100 x 95 mm
Supported languages	...	...	...	Polish, English, French, Spanish, German, Portuguese, Russian, Italian
Manufacturer / Brand	...	UBIQUITI	...	DAHUA
Guarantee	2 years	2 years	2 years	3 years