





	<a href="#">PATCHCORD RJ45/6/15- GREY 15 m</a>	<a href="#">METER OF CAPACITANCE, INDUCTANCE AND RESISTANCE UT-603</a>	<a href="#">GROUNDING RESISTANCE METER UT-522 UNI-T</a>
			
	6.89 CAD 6.89 CAD	78.74 CAD 78.74 CAD	287.78 CAD 287.78 CAD
DC voltage measurement	...	—	...
AC voltage measurement	...	—	...
DC current measurement	...	—	...
AC current measurement	...	—	...
Cable	UTP cat. 6 : RJ-45 Plug / RJ-45 Plug	...	...
Color	Gray	...	...
Length of the cable	15 m	...	...
Ground voltage measurement	...	...	400 V ± (1.0% + 6) @ 1 V
Automatic change of measuring ranges	...	...	—
USB	...	...	—
Resistance measurement	...	200 Ω ± (0.8% + 3) @ 0.1 Ω , 2 kΩ ± (0.8% + 1) @ 0.001 kΩ , 20 kΩ ± (0.8% + 1) @ 0.01 kΩ , 200 kΩ ± (0.8% + 1) @ 0.1 kΩ , 2 MΩ ± (0.8% + 1) @ 0.001 MΩ , 20 MΩ ± (2.0%(RD-12) + 5) @ 0.01 MΩ 2000 MΩ @ 1 MΩ - visual measurement	40 Ω ± (2% + 20) @ 0.01 Ω , 400 Ω ± (2% + 3) @ 0.1 Ω , 4000 Ω ± (2% + 3) @ 1 Ω • Auxiliary resistance : 500 Ω ± 5 % • Measuring voltage : ≤ 10 V AC @ ~820 Hz
Operation temp	...	...	5 °C ... 40 °C
Permissible relative humidity	...	...	≤ 80 % (non-condensing)

Capacitance measurement	...	2 nF ± (1% + 5) @ 0.001 nF , 20 nF ± (1% + 5) @ 0.01 nF , 200 nF ± (1% + 5) @ 0.1 nF , 2 μF ± (4% + 5) @ 0.001 μF , 20 μF ± (4% + 5) @ 0.01 μF , 200 μF ± (4% + 5) @ 0.1 μF , 600 μF @ 1 μF - visual measurement	...
Inductance measurement	...	2 mH ± (2% + 8) @ 0.001 mH , 20 mH ± (2% + 8) @ 0.01 mH , 200 mH ± (2% + 8) @ 0.1 mH , 2 H ± (5% + 5) @ 0.001 H , 20 H ± (5% + 5) @ 0.01 H , 200 H @ 0.1 H - visual measurement	...
Frequency measurement	...	—	...
Square-wave signal duty ratio measurement	...	—	...
Temperature measurement	...	—	...
hFE	...	✓	...
Diode test	...	✓	...
Sound signal of the continuity test	...	✓	...
Checking TTL logic states	...	—	...
RS-232	...	—	—
Main features	<ul style="list-style-type: none"> <li>• Very easy and quick assembly</li> <li>• Aluminum coated with copper - CCA, AWG 26</li> </ul>	<ul style="list-style-type: none"> <li>• Large, readable LCD display with backlight</li> <li>• Hold - stopping the meter reading</li> <li>• Aesthetic and solid construction</li> </ul>	<ul style="list-style-type: none"> <li>• Hold - stopping the meter reading,</li> <li>• The measurement can be performed in full or simplified configuration,</li> <li>• Warning of poor connection of leads during measurement,</li> <li>• Large, readable LCD display with backlight,</li> <li>• Low battery level alarm,</li> <li>• Aesthetic and solid construction,</li> <li>• The set includes a practical case</li> </ul>
Power supply	...	9V, type 6LR61 battery - included	6 x 1.5V, type AA/LR6/FR6 battery - included

Weight	0.50 kg	0.29 kg	0.42 kg
Dimensions	...	172 x 84 x 41 mm	160 x 100 x 70 mm
Manufacturer / Brand	...	UNI-T	UNI-T
Guarantee	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00