



	IP CAMERA IPC3614SS-ADF28KM-I0-BLACK - 4 Mpx 2.8 mm UNIVIEW	SLOTTED SCREWDRIVER 6.5 ST-0-64-917 STANLEY
		
	2080.66 DKK 2080.66 DKK	19.06 DKK 19.06 DKK
Standard	TCP/IP	...
Tip size	...	6.5 mm
Arrowhead length	...	45 mm
Sensor	1/2.7 " Progressive Scan CMOS	...
Voltage insulation	...	—
Matrix size	4 Mpx	...
Scanning system	Progressive	...
Main features	...	<ul style="list-style-type: none"> • Magnetic tip • High-quality chrome-vanadium steel bar protects against corrosion and reduces the chance of tip breakage • Ergonomically designed bi-material handle reduces fatigue, improves efficiency • Large diameter handle offers great torque
Resolution	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p	...
Lens	2.8 mm	...
View angle	<ul style="list-style-type: none"> • 96 ° (manufacturer data) • 92 ° (our tests result) 	...
Range of IR illumination	40 m	...
S/N ratio	> 52 dB	...
RS-485 interface	—	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...
Image compression method	Ultra 265 / H.265 / H.264 / MJPEG	...
Alarm inputs / outputs	—	...
Audio	<ul style="list-style-type: none"> • Microphone built-in • Audio transmission via network • Audio detection 	...
Main stream frame rate	25 fps @ 4 Mpx	...
Network interface	10/100 Base-T (RJ-45)	...
WEB Server	Built-in	...
Max. number of on-line users	32	...

ONVIF	✓	...
Mobile phones support	Access by a cloud (P2P) • Android: Free application EZView • iOS (iPhone): Free application EZView	...
Default IP address	DHCP or 192.168.1.13	...
Default admin user / password	admin / 123456	...
Web browser access ports	80, 554	...
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation	...
Mobile client access ports	80	...
Port ONVIF	80	...
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream	...
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • BLC/HLC - Back Light / High Light Compensation • Image rotation and mirror • Privacy zones - max. 4 • Motion detection with human/vehicle silhouette recognition • Sharpness - sharper image outlines • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, abandoned/missing object, face detection, people counting, crowd gathering estimation, scene changing 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 330 mA 	...
Power consumption	≤ 4 W	...
Housing	Dome, Metal	...

Color	Black	...
"Index of Protection"	IP67	...
Vandal-proof	—	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.44 kg	0.044 kg
Dimensions	Ø 111 x 94 mm	Ø 30 x 105 mm
Supported languages	Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian	...
Manufacturer / Brand	UNIVIEW	STANLEY
Guarantee	3 years	2 years