



| | | |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| | IP CAMERA DS-2CD1T47G2H-LIU(2.8MM) ColorVu - 4 Mpx Hikvision | ACCESS POINT +ROUTER ACB-ISP Wi-Fi 2.4 GHz 300 Mbps UBIQUITI |
| |  |  |
| | 211.86 EUR 211.86 EUR | 37.64 EUR 37.64 EUR |
| Frequency range | ... | 2.4 GHz |
| Standard | IP | ... |
| Antenna type | ... | 2x2 MIMO - built-in 4 dBi |
| Standards | ... | IEEE 802.11n, Wi-Fi |
| Baud rates | ... | 300 Mbps |
| Resolution | 2560 x 1440 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p | ... |
| Protections | ... | WPA2 |
| Sensor | 1/3 " Progressive Scan CMOS | ... |
| LAN ports | ... | 4 x 10/100 Mbps |
| Lens | 2.8 mm | ... |
| View angle | 115 ° | ... |
| Transmitter power | ... | 19 dBm (max) |
| White light LED illuminator range | 50 m | ... |
| Power supply PoE | ... | Ubiquiti Passive PoE |
| Range of IR illumination | 50 m | ... |
| Memory card slot | — | ... |
| Image compression method | H.265+ / H.265 / H.264+ / H.264 / MJPEG | ... |
| Alarm inputs / outputs | — | ... |
| Audio | <ul style="list-style-type: none"> • Microphone built-in, • Audio transmission via network | ... |
| Main stream frame rate | 20 fps @ 4 Mpx | ... |
| Interface | 10/100 Base-T (RJ-45) | ... |
| WEB Server | Built-in | ... |
| Max. number of on-line users | 6 | ... |
| ONVIF | ✓ | ... |

| | | |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Main features | ... | <ul style="list-style-type: none"> • PoE OUT 24 V - port WAN, (4, 5+; 7, 8-) • Port Security : Contact/Air (ESD/EMP) \pm 24 kV / \pm 24 kV • Easy and uniform management system for many devices • Intuitive installation and configuration of many advanced functions • MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network |
| Operation temp | ... | -10 °C ... 50 °C |
| Permissible relative humidity | ... | 5 % ... 95 % |
| Main features | <ul style="list-style-type: none"> • Smart Hybrid Light / ColorVu technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Possibility to change the resolution, quality and bit rate • Horizontal mirror image • Smart motion detection (with recognizing people and vehicles) • Configurable Privacy Zones • Sharpness - sharper image outlines • video tampering • Filtering of false alarms based on the recognition of persons and vehicles | ... |
| Mobile phones support | Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect | ... |
| Default IP address | 192.168.1.64 | ... |
| Default admin user / password | admin / - The administrator password should be set at the first start | ... |
| Web browser access ports | 80 | ... |
| PC client access ports | Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application | ... |
| Mobile client access ports | 8000 | ... |
| Port ONVIF | 80 | ... |

| | | |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| RTSP URL | <ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ | ... |
| Power supply | <ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 570 mA | <ul style="list-style-type: none"> • 4.95 ... 5.05 V DC / 2 A - micro USB socket (power adapter not included) • PoE 24 V - Port 1 |
| Power consumption | <ul style="list-style-type: none"> • ≤ 8.3 W @ PoE • ≤ 6.8 W @ 12 V DC | ≤ 5 W |
| Housing | Compact, Metal | ... |
| Color | White | ... |
| "Index of Protection" | IP67 | ... |
| Mechanical protection class | — | ... |
| Operation temp | -30 °C ... 60 °C | ... |
| Weight | 0.41 kg | 0.22 kg |
| Dimensions | 202 x 84 x 81 mm | 89 x 90 x 89 mm |
| Supported languages | Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian | ... |
| Manufacturer / Brand | Hikvision | UBIQUITI |
| SAP Code | 311325498 | ... |
| Guarantee | 3 years | 2 years |