

| | | | | | |
|-----------------------------------|---|---|---|--|---|
| | SWITCH POE DS-3E0518P-E 16-PORT SFP Hikvision | POWER SUPPLY ADAPTER PSC-12010/PRO 12 V DC 1 A | AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1200TLM-IL-A-0360B-S6 - 1080p 3.6 mm DAHUA | EXPANSION PLUG JPK-12X220/M5 EBOLT | CONNECTOR STRIP KE-2273-205/WAGO |
| |  |  |  |  |  |
| | 2204.91 DKK 2204.91 DKK | 54.45 DKK 54.45 DKK | 560.63 DKK 560.63 DKK | 14.69 DKK 14.69 DKK | 1.49 DKK 1.49 DKK |
| Number of terminal pairs | ... | ... | ... | ... | 1 |
| Adapter type | ... | Switching | ... | ... | ... |
| Connector type | ... | ... | ... | ... | 5 x spring terminal |
| Output voltage | ... | 12 V DC | ... | ... | ... |
| Maximal load | ... | 1 A | ... | ... | ... |
| Standard | ... | ... | AHD, HD-CVI, HD-TVI, CVBS | ... | ... |
| Average active efficiency | ... | 83 % | ... | ... | ... |
| Sensor | ... | ... | Progressive Scan CMOS | ... | ... |
| Wire gauge | ... | ... | ... | ... | 0.5 ... 2.5 mm ² - Wire |
| Output power | ... | 12 W | ... | ... | ... |
| Matrix size | ... | ... | 2.1 Mpx | ... | ... |
| Nominal voltage | ... | ... | ... | ... | 450 V |
| Power consumption at no-load | ... | < 0.1 W | ... | ... | ... |
| Material | ... | ... | ... | <ul style="list-style-type: none"> Expansion plug, Polypropylene Screw, Steel galvanized mounting screw, Steel galvanized | ... |
| Rated current | ... | ... | ... | ... | 24 A |
| Number of outputs | ... | 1 pcs | ... | ... | ... |
| Drilling diameter | ... | ... | ... | 12 mm | ... |
| Expansion plug length | ... | ... | ... | 215 mm | ... |
| Power connectors type | ... | 2.1/5.5 mm - Straight plug | ... | ... | ... |
| Screw dimensions | ... | ... | ... | Ø 8 x 220 mm, Internal thread M5 | ... |
| Power voltage | ... | 100 ... 240 V AC | ... | ... | ... |
| Housing type | ... | Plastic | ... | ... | ... |
| Screw | ... | ... | ... | Ø 5 x 16 mm | ... |
| LAN ports | <ul style="list-style-type: none"> • 16 x RJ45 10/100/1000 Base-TX (16 x PoE (802.3af/at)), • 1 x RJ45 10/100/1000 Base-TX - Uplink, • 1 x port SFP 10/100/1000 Base-TX - Uplink | ... | ... | ... | ... |
| Application | ... | ... | ... | for Styrofoam 150 mm | ... |
| Resolution | ... | ... | 1920 x 1080 - 1080p @ HD-CVI / HD-TVI / AHD @ 25 fps , 960 x 576 - 960H @ PAL @ 25 fps | ... | ... |
| Lens | ... | ... | 3.6 mm | ... | ... |
| Transmission speed | <ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps - 16 LAN & PoE ports, • 10 / 100 / 1000 Mbps - 2 Uplink ports | ... | ... | ... | ... |
| Maximal output power | 30 W / port PoE | ... | ... | ... | ... |
| Maximal total power | 230 W | ... | ... | ... | ... |
| View angle | ... | ... | <ul style="list-style-type: none"> • 83 ° (manufacturer data) • 84 ° (our tests result) | ... | ... |
| MAC addresses table | 8k | ... | ... | ... | ... |
| Range of IR illumination | ... | ... | 40 m | ... | ... |
| Management | — | ... | ... | ... | ... |
| White light LED illuminator range | ... | ... | 40 m | ... | ... |

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

| | | | | | |
|---------------------------------|---|--|--|---------|---|
| IR illuminator power adjustment | ... | ... | Automatic | ... | ... |
| Main features | <ul style="list-style-type: none"> • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Overvoltage protection : 6 kV - PoE ports • Can be mounted in a Rack 19" cabinet | <ul style="list-style-type: none"> • Short-circuit protection • Overload protection • The device has very small dimensions • Length of the cables : 40 + 15 cm | ... | ... | The product has a special measuring gap designed for voltage tester or cables of the tester |
| Video output | ... | ... | AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω | ... | ... |
| LED diodes | Power, Link/Act, PoE, PoE Max | ... | ... | ... | ... |
| Audio | ... | ... | <ul style="list-style-type: none"> • Microphone built-in, • Audio support via coaxial cable - HD-CVI only | ... | ... |
| Certificates | CE, FCC, RoHS | ... | ... | ... | ... |
| OSD menu | ... | ... | ✓ | ... | ... |
| Operation temp | -10 °C ... 55 °C | 0 °C ... 40 °C | ... | ... | ... |
| Main features | ... | ... | <ul style="list-style-type: none"> • Smart Dual Illumination technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Privacy zones - max. 8 • Mirror - Mirror image • Auto White Balance • Sharpness - sharper image outlines | ... | ... |
| SAP Code | 301801378 | ... | ... | ... | ... |
| Power supply | 100 ... 240 V AC | ... | 12 V DC / 340 mA | ... | ... |
| Power consumption | ... | ... | ≤ 4.1 W | ... | ... |
| Housing | Metal | ... | Compact Plastic + Metal | ... | ... |
| Color | ... | ... | White | ... | Yellow |
| "Index of Protection" | ... | IP67 | IP67 | ... | ... |
| Vandal-proof | ... | ... | — | ... | ... |
| Operation temp | ... | ... | -40 °C ... 60 °C | ... | ... |
| Weight | 2.6 kg | 0.12 kg | 0.3 kg | ... | ... |
| Dimensions | 440 x 221 x 44 mm | 57 x 40 x 26 mm | 198 x 80 x 76 mm | ... | 16 x 21 x 4 mm |
| Manufacturer / Brand | Hikvision | ... | DAHUA | EBOLT | ... |
| Guarantee | 3 years | 2 years | 3 years | 2 years | 2 years |