






	ACCESS CONTROLLER MC16-PAC-ST-2-KIT ROGER	TV OR MONITOR MOUNT BRATECK-LCD-501N	POWER DISTRIBUTION UNIT LE-049475 (4 OUTLETS) 1.5 m LEGRAND	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1801R-Z- A-27135-S2 - 8.3 Mpx, 4K UHD 2.7 ... 13.5 mm - MOTOZOOM DAHUA	BLANK MODULE AD- LS/ZP-45X45 System 45
					
	527.64 EUR 527.64 EUR	3.55 EUR 3.55 EUR	12.44 EUR 12.44 EUR	214.18 EUR 214.18 EUR	0.76 EUR 0.76 EUR
Application	System 45
Material	Plastic
Number of served transitions	2 (two-way)
Rated voltage	230 V AC / 50 Hz
Total maximal current	16 A
Number of supported readers	8
Mounting standard	...	VESA 75, 100
Maximal total load	3680 W
Screen size range	...	max. 32 "
Standard	AHD / HD-CVI / HD-TVI / PAL	...
Number of outlets	4 grounded outlets 16A/250V CEE 7/5
Number of users	unlimited (purchase of the appropriate license required)
Bearing capacity	...	30 kg
Sensor	Progressive Scan CMOS	...
Fuse	—
Distance from mounting surface	...	88 mm from wall
Matrix size	8.3 Mpx 4K UHD	...
Switch	—
Number of media per ID	8 - Proximity card, PIN code, fingerprint, etc.
Wire gauge	3 x 1.0 mm ²
Buffer memory	8 000 000 events buffer
Length of the cable	1.5 m
Number of access zones	4
Tilt adjustment	...	-15 ° ... 15 °
Number of alarm zones	4
Horizontal rotation	...	-24 ° ... 24 °
Battery backup support	12 V / 20 Ah
Rotation in the plane of the screen	...	—
Communication	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RACS 5 v2 (Roger) • RS-485 interface
Resolution	3840 x 2160 - 8.3 Mpx, 4K UHD @ 15 fps, 2880 x 1620 - 5 Mpx @ 25 fps, 2560 x 1440 - 4 Mpx @ 25 fps, 1920 x 1080 - 1080p, 960 x 576 - 960H, PAL	...

Main features	<ul style="list-style-type: none"> • Metal housing • The MCX2D I/O expander included • Integrated support in VISO ST software • Functions in the VISO ST system: <ul style="list-style-type: none"> - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system : 128
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	...
Operation temp	5 °C ... 40 °C
Lens	2.7 ... 13.5 mm - Motozoom, AutoFocus	...
Permissible relative humidity	10 % ... 95 % (non-condensing)
View angle	114 ° ... 32 °	...
Range of IR illumination	80 m	...
IR illuminator power adjustment	Automatic	...
Audio	<ul style="list-style-type: none"> • Microphone built-in • Audio support via coaxial cable - HD-CVI only 	...
Main features	<ul style="list-style-type: none"> • Motozoom lens - AutoFocus • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • D-ZOOM - Digital Zoom : 4x • Auto White Balance • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Configurable Privacy Zones • Mirror - Mirror image • Sharpness - sharper image outlines 	...
OSD menu	✓	...
Power supply	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC 	12 V DC / 890 mA	...
Power consumption	≤ 10.6 W	...
Housing	Plastic	Compact, Metal	...
Color	...	Black	White / Light gray	White + Black	White
"Index of Protection"	IP67	...
Operation temp	-30 °C ... 60 °C	...
Weight	4.25 kg	0.524 kg	0.33 kg	0.57 kg	0.006 kg
Dimensions	405 x 365 x 123 mm	115 x 115 x 88 mm	208 x 53 x 38 mm	210 x 90 x 90 mm	45 x 45 x 16 mm
Manufacturer / Brand	ROGER	BRATECK	LEGRAND	DAHUA	STASINSKI / JAVEL
Guarantee	3 years	2 years	2 years	3 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00