



| | ACCESS CONTROLLER MODULE MC16-PAC-EX-16 ROGER | SWITCH TL-LS1005G 5- PORT TP-LINK |
|---------------------------------|--|--|
| |  |  |
| | 2944.40 EUR 2944.40 EUR | 13.33 EUR 13.33 EUR |
| LAN ports | ... | 5 x (RJ45) 10/100/1000 Mb Auto-Negotiation, Auto MDI/MDIX |
| Number of served transitions | 16 (two-way) | ... |
| Number of supported readers | 64 | ... |
| Number of users | limited by license (max. no limit) | ... |
| Number of media per ID | 8 - Proximity card, PIN code, fingerprint, etc. | ... |
| Management | ... | — |
| Buffer memory | 8 000 000 events buffer | ... |
| Number of access zones | 32 | ... |
| LED diodes | ... | Power, Link/Act |
| Number of alarm zones | 32 | ... |
| Transmission speed | ... | 10 / 100 / 1000 Mbps - Gigabit Ethernet |
| Battery backup support | 12 V / 7 Ah | ... |
| Jumbo Frame | ... | 16 kB |
| MAC addresses table | ... | 2 k |
| Communication | <ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RACS 5 v2 (Roger) • RS-485 interface | ... |
| Certificates | ... | CE, FCC, RoHS |
| Housing | ... | Plastic, Desktop |
| Power consumption | ... | max. 3.7 W |

| | | |
|-------------------------------|--|--|
| Main features | <ul style="list-style-type: none"> • Integrated support in VISO EX software • Functions in the VISO EX system: <ul style="list-style-type: none"> - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system - unlimited - division of the system into partitions operated by independent operators - tool for integration with RACS5 (API) systems - integration with many systems (elevator systems, building applications, SMS, BMS, PSIM, VMS, Active Directory systems) | <ul style="list-style-type: none"> • LiteWave product series • Auto MDI/MDX • Auto-learning and Auto-aging functions support for MAC addresses • Support for bandwidth control in full duplex (IEEE802.3x) and a back pressure function in half-duplex mode • Green TP-LINK technology - big energy saving • Box casing designed to wall mounting |
| Power supply | <ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC | 5 V DC / 600 mA (power adapter included) |
| Operation temp | 5 °C ... 40 °C | 0 °C ... 40 °C |
| Permissible relative humidity | 10 % ... 95 % (non-condensing) | 10 % ... 90 % |
| Weight | 0.14 kg | 0.07 kg |
| Dimensions | 175 x 72 x 30 mm | 90 x 72 x 23 mm |
| Manufacturer / Brand | ROGER | TP-LINK |
| Guarantee | 3 years | 3 years |