

	<a href="#">Black body DS-2TE127-G4A Hikvision</a>	<a href="#">IP CAMERA APTI-AI805VA2-28W-L Full-Color - 8.3 Mpx 4K UHD 2.8 mm</a>	<a href="#">COUPLER GG-5.5</a>
			
	4413.08 EUR 4413.08 EUR	114.88 EUR 114.88 EUR	0.59 EUR 0.59 EUR
Standard	...	TCP/IP	...
Matrix size	...	8.3 Mpx	...
Adjusting the reference temperature	5 °C ... 50 °C	...	...
Setting resolution	0.1 °C	...	...
Sensor	...	1/2.8 " SONY Starvis™ Back-illuminated CMOS	...
Setting accuracy	± 0.1 °C	...	...
Setting stability	± 0.1 °C/h	...	...
Connector type	...	...	Coupler Socket 2.1 : 5.5 mm / Socket 2.1 : 5.5 mm
Effective Emissivity	0.97 ± 0.02	...	...
Size of the reference surface	Ø 70 mm	...	...
Material	...	...	Metal / PET
Main features	Possibility to mount on a tripod - 1/4" thread	...	<ul style="list-style-type: none"> <li>• Very easy and quick assembly</li> <li>• Corrosion resistance</li> </ul>
Operation temp	0 °C ... 40 °C	...	...
Resolution	...	3840 x 2160 - 8.3 Mpx 4K UHD , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	...
Lens	...	2.8 mm	...
View angle	...	105 °	...
White light LED illuminator range	...	30 m	...
SAP Code	315800009	...	...
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Main stream frame rate	...	25 fps @ 8.3 Mpx	...
Network interface	...	10/100 Base-T (RJ-45)	...
Memory card slot	...	—	...
Alarm inputs / outputs	...	—	...
Audio	...	<ul style="list-style-type: none"> <li>• External microphone input - Jack 3.5 mm socket</li> <li>• Audio output - Jack 3.5 mm socket</li> <li>• Audio transmission via network</li> <li>• Compliance with the AAC standard</li> </ul>	...

WEB Server	...	Built-in	...
Max. number of on-line users	...	10	...
ONVIF	...	19.12	...
RS-485 interface	...	—	...
Mobile phones support	...	Port no.: 80 or access by a cloud (P2P) • Android: Free application <a href="#">BitVision</a> • iOS (iPhone): Free application <a href="#">BitVision</a>	...
Default IP address	...	192.168.1.168	...
Default admin user / password	...	admin / admin The administrator password should be set at the first start	...
Web browser access ports	...	80	...
PC client access ports	...	80	...
Mobile client access ports	...	80	...
Port ONVIF	...	80	...
RTSP URL	...	rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream	...
Main features	...	<ul style="list-style-type: none"> <li>• WDR - 140 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• Flicker Control - The technology eliminates the tiring eyes flickering image effect</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• ICR - Movable InfraRed filter</li> <li>• Privacy zones</li> <li>• Image rotation and mirror</li> <li>• Sharpness - sharper image outlines</li> <li>• Intelligent image analysis : intrusion, crossing the line (tripwire), detection of people gathering, loitering detection, motion detection based on human detection</li> <li>uploading face captures to FTP</li> </ul>	...



Power supply	100 V ... 240 V AC	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 450 mA</li> </ul>	...
Power consumption	≤ 20 W	≤ 5.4 W	...
Housing	...	Dome - Metal	...
Color	...	White	...
"Index of Protection"	...	IP67	...
Vandal-proof	...	—	...
Operation temp	...	-20 °C ... 60 °C	...
Weight	1.85 kg	0.5 kg	0.006 kg
Dimensions	177 x 120 x 120 mm	Ø 97 x 91 mm	Ø 10 x 40 mm
Supported languages	...	Polish, English, Bulgarian Czech, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian	...
Manufacturer / Brand	Hikvision	APTI	...
Guarantee	3 years	2 years	2 years

