






	CAMERA CEILING BRACKET TR-CM06-D UNIVIEW	IP VANDALPROOF CAMERA IPC3634SB-ADZK-10-BLACK - 4 Mpx 2.7 ... 13.5 mm - MOTOZOOM UNIVIEW	CONNECTOR STRIP WAGO-222-415*P40	ISOPROPYL ALCOHOL KONTAKT-IPA-PLUS/5000 METAL CANISTER 5 l AG TERMOPLASTY	DOUBLE INTERMEDIATE SWITCH DW7/2.01/X/49-SIMON54 250 V 10 A
					
	15.41 AUD 15.41 AUD	713.46 AUD 713.46 AUD	42.08 AUD 42.08 AUD	46.46 AUD 46.46 AUD	27.69 AUD 27.69 AUD
Suitable for cameras	UNIVIEW
Standard	...	TCP/IP
Material	Aluminum
Package	Metal canister 5 l	...
Sensor	...	1/3 " Progressive Scan CMOS
Device type	Double Intermediate Switch (bistable)
In package	40 pcs The price for package
Matrix size	...	4 Mpx
Number of terminal pairs	1
Rated voltage	250 V AC
Connector type	5 x spring terminal
Connectors type	Quick-connector
Application	Ideal for removing dirt from optical components	Flush-mounted, Simon 54 product series, for Nature, Premium frames
Backlight	—
Wire gauge	• 0.08 ... 2.5 mm ² - Wire, • 0.08 ... 4 mm ² - Stranded wire
Assembly	Claw or screw mounting
Nominal voltage	400 V
Resolution	...	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p
Rated current	32 A	...	10 A (inductive load)
Main features	The product is reusable
Lens	...	2.7 ... 13.5 mm - Motozoom, AutoFocus
View angle	...	• 98 ° ... 31 ° (manufacturer data) • 100 ° ... 28 ° (our tests result)
Range of IR illumination	...	40 m
RS-485 interface	...	—
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Image compression method	...	Ultra 265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	...	—
Audio	...	• Microphone built-in • Audio transmission via network • Audio detection
Main stream frame rate	...	25 fps @ 4 Mpx
Network interface	...	10/100 Base-TX (RJ-45)
Network protocols	...	IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, IEEE 802.1x, SNMP, QoS, SSL / TLS, SSH
WEB Server	...	Built-in
Max. number of on-line users	...	32
ONVIF	...	✓
Mobile phones support	...	Access by a cloud (P2P) • Android: Free application EZView • iOS (iPhone): Free application EZView
Default IP address	...	DHCP or 192.168.1.13

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Default admin user / password	...	admin / 123456
Web browser access ports	...	80, 554
PC client access ports	...	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	...	80
Port ONVIF	...	80
RTSP URL	...	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream
Main features	...	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Day/night mode • Vertical or horizontal image mirror • Motion detection with human/vehicle silhouette recognition • Privacy zones - max. 4 • Intelligent image analysis : intrusion, crossing the line (tripwire), detection of entry into the area / exit from the area, people counting , crowd gathering estimation
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 580 mA
Power consumption	...	≤ 7 W
Housing	...	Dome - Metal	Non-halogen plastic, PC
Color	White	Black	Gray / Orange	...	Matt black
"Index of Protection"	...	IP67	IP20 / IP44 (using frame seal)
Vandal-proof	...	IK10
Operation temp	...	-30 °C ... 60 °C
Weight	0.09 kg	0.69 kg	...	4.371 kg	0.07 kg
Dimensions	131 x 104 x 67 mm	Ø 129 x 110 mm	20.5 x 26.6 x 14.5 mm	315 x 168 x 105 mm	<ul style="list-style-type: none"> • 75 x 75 x 41 mm • 26 mm - mounting depth
Supported languages	...	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovenian, Hungarian, Italian
Manufacturer / Brand	UNIVIEW	UNIVIEW	...	AG TERMOPASTY	KONTAKT Simon
Guarantee	3 years	3 years	2 years	...	6 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00