



	CYLINDRICAL MAGNETIC CONTACT B-2T SATEL	SMART ROLLER GATE CONTROLLER ROLLERGATE/BLEBOX Wi-Fi, 230 V AC
		
	3.11 EUR 3.11 EUR	87.30 EUR 87.30 EUR
Detection	Opening the door or window	...
Application	...	roller gates
Maximum reed switched voltage	100 V	...
Rated voltage	...	230 V AC
Maximal switched current	500 mA	...
Make distance	19 mm	...
Maximal total load	...	2 x 1250 VA
Break distance	20 mm	...
Total maximal current	...	2 x 5 A
Number of inputs	...	<ul style="list-style-type: none"> • 4 control, • 2 security
Number of outputs	...	<ul style="list-style-type: none"> • 2 control, • 1 signaling
Connector type	...	screw terminals
Wireless	...	Wi-Fi, 2.4 GHz - IEEE 802.11g
Mobile phones support	...	<ul style="list-style-type: none"> • The wBox free application on Android • The wBox free application on iOS

Main features	Cable terminals	<ul style="list-style-type: none"> • Roller gate control in cooperation with security modules (photocell, barrier, sensing edge), • Multiple users support from anywhere, • Control many objects from one app, • remote access, • voice control, • Keyboard built-in - 3 Touch control keys, • Backlit, touch control panel • Omnidirectional antenna Wi-Fi 5 dB, • SMA-RP socket • Range : 100 m (in open area), 40 m (internal) • µWiFi technology support
Housing	...	Self-extinguishing , Surface-mounted (box)
"Index of Protection"	...	IP44
Color	White	Gray / Black
Operation temp	...	-20 °C ... 50 °C
Weight	0.02 kg	0.37 kg
Dimensions	19 x 11 mm	<ul style="list-style-type: none"> • 129 x 96 x 57 mm - without antenna • 285 x 96 x 57 mm - with antenna, vertical • 197 mm - Antenna
Manufacturer / Brand	SATEL	BleBox
Guarantee	2 years	2 years