



	<a href="#">CONNECTOR STRIP KE-ZPT5-16.0</a>	<a href="#">UPS AT-UPS850-LED 850 VA EAST</a>
		
	4.37 EUR 4.37 EUR	74.10 EUR 74.10 EUR
Nominal power	...	510 W
Number of terminal pairs	5	...
Apparent Power	...	850 VA
Connector type	terminals	...
Nominal voltage	400 V	...
Input voltage	...	165 V ... 275 V AC
Wire gauge	10 ... 16 mm <sup>2</sup>	...
Dielectric	Plastic	...
Input frequency	...	50 / 60 Hz (auto detection)
Color	Black	...
Output voltage	...	230 V AC ± 10 % (Approximated Sine Wave)
Output frequency	...	50 / 60 Hz ± 1 %
Transfer time	...	≤ 10 ms
Charging time (recover to 90% capacity)	...	8 hours
Battery	...	1 pcs - 12V/8Ah
Estimated battery operation time	...	<ul style="list-style-type: none"> <li>• 23 minutes @ 100 W</li> <li>• 5 minutes @ 300 W</li> <li>• 2 minutes @ 500 W</li> </ul>
Number of outputs	...	2 pcs CEE 7/3 (Schuko)
Protections	...	<ul style="list-style-type: none"> <li>• Fuse</li> <li>• Overvoltage</li> <li>• Overload protection</li> <li>• Overcharge protection</li> <li>• Telephone line filter</li> </ul>
Operation state indication	...	<ul style="list-style-type: none"> <li>• LED diodes,</li> <li>• Sound signaling</li> </ul>
Main features	...	<ul style="list-style-type: none"> <li>• Auto restart while AC is recovering</li> <li>• Automatic Voltage Regulator (AVR)</li> <li>• Compatible with power generators</li> <li>• Remote management - UPSmart application included</li> <li>• Built-in EMI, RFI filter</li> <li>• Configurable alarm</li> </ul>

Application	...	<ul style="list-style-type: none"> <li>• Surveillance Systems</li> <li>• data storage centers</li> <li>• network, servers, workstations</li> <li>• Industrial Equipment</li> </ul>
Housing type	...	Tower
Operation temp. / Relative humidity	...	0 °C ... 40 °C / 20 ... 90 %
Weight	...	6.12 kg
Dimensions	126 x 79 x 26 mm	330 x 163 x 95 mm
Manufacturer / Brand	...	EAST
Guarantee	2 years	2 years