



	<a href="#">POWER SEPARATOR PFM790 DAHUA</a>	<a href="#">VIDEO SEPARATOR D- SEP2/HD</a>
		
	7238.10 HUF 7238.10 HUF	2436.19 HUF 2436.19 HUF
Input voltage	12 V DC $\pm$ 20 %	...
Output voltage	12 V DC $\pm$ 5 %	...
Output current	max. 400 mA	...
Input socket type	2.1/5.5 mm socket	...
Output socket type	2.1/5.5 mm plug	...
Current consumption	90 mA	...
Standard	...	<ul style="list-style-type: none"> <li>• AHD - 8 Mpx, 4K UHD</li> <li>• HD-CVI - 8 Mpx, 4K UHD</li> <li>• HD-TVI - 8 Mpx, 4K UHD</li> <li>• CVBS - PAL / NTSC</li> </ul>
Efficiency	85 % @ 400 mA	...
Device type	...	Passive
Number of inputs	1	1 pcs BNC socket
Number of outputs	1	1 pcs BNC plug
Input impedance	...	75 $\Omega$
Output impedance	...	75 $\Omega$
Opto-isolation between inputs and outputs	...	16 V DC
Manufacturer / Brand	DAHUA	...
Attenuation	...	<ul style="list-style-type: none"> <li>• 4.43 MHz @ 0.21 dB</li> <li>• 11 MHz @ 0.41 dB</li> <li>• 21 MHz @ 0.82 dB</li> <li>• 38 MHz @ 1.19 dB</li> <li>• 42 MHz @ 1.17 dB</li> <li>• 67.5 MHz @ 3.46 dB</li> </ul>
Insertion loss	...	0.5 dB
Bandwidth	...	180 MHz
Power supply	...	—
Operation temp	-30 °C ... 60 °C	-20 °C ... 55 °C
Weight	0.032 kg	0.03 kg
Dimensions	108 x 22 x 20 mm	60 x 28 x 22 mm
Guarantee	3 years	2 years