




	IP CAMERA BCS-B-EIP12FR3(2.0) - 1080p 2.8 mm BCS BASIC	CARBON MONOXIDE DETECTOR TESTER DG-TEST-2 SATEL	POWER DISTRIBUTION UNIT ACAR-ECO-PLUS (6 OUTLETS)
			
	1078.91 CZK 1078.91 CZK	530.21 CZK 530.21 CZK	1493.59 CZK 1493.59 CZK
Application	...	Carbon Monoxide (CO) detectors	...
Standard	TCP/IP
Maximal load power	2300 W
In the kit	...	5 pcs	...
Sensor	1/2.8 " Progressive Scan CMOS
Matrix size	2.1 Mpx
Nominal voltage	230 V AC / 50 Hz
Fuse	10 A / 250 V
Switch	two-way
Leak current	< 0.5 mA
Response time	< 25 ns
Resolution	1920 x 1080 - 1080p , 1280 x 720 - 720p
Nominal voltage of surge suppressor	250 V
Lens	2.8 mm
Protection level	1.3 kV (L/N)
Nominal stroke current	2 kA (L/N) - (8/20µs)
View angle	<ul style="list-style-type: none"> • 107 ° (manufacturer data) • 94 ° (our tests result)
Range of IR illumination	30 m
Maximum stroke current	6.5 kA (L/N) - (8/20µs)
S/N ratio	> 52 dB
Electric shock protection system	Ground connectors (pins) connected with ground wire of AC mains
RS-485 interface	—
Memory card slot	—
Number of output outlets	<ul style="list-style-type: none"> • 1 MASTER outlet, two-contact with ground contact • 3 SLAVE outlets with auto switch off the power supply after switch off the receiver powered from MASTER outlet • 2 outlets separate from MASTER outlet

Length of the cable	1.45 m
Image compression method	H.265+ / H.265 / H.264+ / H.264
Alarm inputs / outputs	—
Audio	<ul style="list-style-type: none"> • Microphone built-in • Audio transmission via network • Audio detection
Main stream frame rate	25 fps @ 1080p
Network interface	10/100 Base-T (RJ-45)
Network protocols	IPv4, IGMP, ICMP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, UPnP, HTTP, RTMP
WEB Server	Built-in
Max. number of on-line users	4
ONVIF	✓
Mobile phones support	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application BCS Manager • iOS (iPhone): Free application BCS Manager
Default IP address	DHCP or 192.168.1.13
Default admin user / password	admin / 123456
Web browser access ports	80, 554
PC client access ports	Port no.: 80 or access by a cloud (P2P)
Mobile client access ports	80
Port ONVIF	80
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream
Main features	<ul style="list-style-type: none"> • 2D-DNR, 3D-DNR - Digital Noise Reduction • D-WDR - Wide Dynamic Range • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • D-ZOOM - Digital Zoom • Possibility to change the resolution, quality and bit rate • Configurable Privacy Zones • Motion Detection • Mirror - Mirror image
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 300 mA
Power consumption	≤ 3.5 W



Housing	Dome - Plastic + Metal	...	Plastic - non-flammable
Color	White
"Index of Protection"	IP67
Vandal-proof	—
Operation temp	-30 °C ... 60 °C
Weight	0.26 kg	0.001 kg	0.56 kg
Dimensions	Ø 118 x 97 mm	Ø 12 x 55 mm	447 x 55 x 53 mm
Supported languages	Polish, English
Manufacturer / Brand	BCS BASIC	SATEL	...
Guarantee	3 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00