

	<a href="#">CABLES TESTER CS-NT24</a>	<a href="#">WEATHER STATION UT-A12T UNI-T</a>	<a href="#">SMART LED LIGHTING CONTROLLER PIXELBOX/BLEBOX Wi-Fi 5 ... 12 V DC</a>
			
	128.85 EUR 128.85 EUR	14.13 EUR 14.13 EUR	22.69 EUR 22.69 EUR
Measurement	...	Temperature / relative humidity	...
Application	...	...	Works with LED lighting - digital (ARGB/RGB) 12V WS2811/WS2815 LED strips
Measurement range	...	-10 °C ... 50 °C ± 1 °C	...
Tested cables	STP / UTP cat. 5, 5e, 6, 6e - RJ45 (8P8C), RJ11 (6P4C), Coaxial cable	...	...
Rated voltage	...	...	5 ... 12 V DC
Measurement of humidity	...	20 % ... 95 % ± 5 %	...
Maximal total load	...	...	60 W (power) , 20 mA (controlling)
Total maximal current	...	...	5 A
Number of inputs	...	...	1
Number of outputs	...	...	1 (power) , 1 (controlling)
Connector type	...	...	screw terminals
Typical battery charge time	3 h	...	...
Backup time	16 h	...	...
Wireless	...	...	Wi-Fi, 2.4 GHz - IEEE 802.11g
Mobile phones support	...	...	<ul style="list-style-type: none"> <li>• The <a href="#">wBox</a> free application on Android</li> <li>• The <a href="#">wBox</a> free application on iOS</li> </ul>

Power supply	Cables tester : Li-Ion battery 3.7 V / 2000 mAh, USB DC 5V/2A power adapter (included) Probe : 2 x 1.5V, type AA/LR6/FR6 battery (not included)	1 x battery LR3 (AAA) (included)	...
Permissible relative humidity	...	max. 90 % (non-condensing)	...
Main features	<ul style="list-style-type: none"> <li>• 2.4 " LCD display - 320 x 240 px</li> <li>• Cable test and cable tracer : cable type, UTP cable's sequence and type test, the fault of RJ45 connector</li> <li>• Test TDR - RJ45 : pair status, length, attenuation, reflectivity, impedance, skew - Length of the cable max. 180 m</li> <li>• Detection of the connected port in switch</li> <li>• Test PING : correct operation of the IP camera's Ethernet port, correct IP address</li> <li>• IP Scan</li> <li>• Identification of the network port and duplex mode</li> <li>• Identification the wire in the group of wires</li> <li>• Telephone line condition detection</li> <li>• Automatic power-off : 10 ... 120 minutes</li> </ul>	<ul style="list-style-type: none"> <li>• LCD display</li> <li>• Digital sensor</li> <li>• External temperature measuring probe : Length of the cable 2 m</li> <li>• Alarm function</li> <li>• Selectable measurement unit: °C / °F</li> <li>• Wall mounting</li> <li>• Integrated stand</li> </ul>	<ul style="list-style-type: none"> <li>• Local control by physical button,</li> <li>• schedule,</li> <li>• timer,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• Controlling the color, effect, changing time allows any interior arrangement</li> <li>• predefined effects,</li> <li>• effects modification,</li> <li>• Possibilities of controlling a digital LED strip consisting of 360 diodes, groups or matrices</li> <li>• Possibility to cut off the power supply of the LED strip when it is switched off (energy saving)</li> <li>• µWiFi technology support</li> </ul>
Housing	...	...	Plastic
"Index of Protection"	...	...	IP20
Color	...	White	Black
Operation temp	...	-10 °C ... 50 °C	-20 °C ... 50 °C
Weight	0.28 kg - Cables tester 0.11 kg - Probe	0.106 kg	0.02 kg
Manufacturer / Brand	...	UNI-T	BleBox
Dimensions	175 x 88 x 40 mm - Cables tester 220 x 47 x 32 mm - Probe	Ø 130 x 78 mm x 22 mm	36 x 26 x 19 mm
Guarantee	2 years	2 years	2 years