





	POWER SUPPLY ADAPTER PSC-12010/PRO 12 V DC 1 A	AHD, HD-CVI, HD-TVI, CVBS CAMERA HAC-HFW1239TU-Z-A-LED-27135-S2 Full-Color - 1080p 2.7 ... 13.5 mm DAHUA	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HDW1500T-IL-A-0280B-S2 - 5 Mpx 2.8 mm DAHUA	HDD FOR DVR HDD-ST6000VX009 6TB 24/7 SkyHawk SEAGATE
				
	83.11 NOK 83.11 NOK	2022.96 NOK 2022.96 NOK	1107.16 NOK 1107.16 NOK	1702.57 NOK 1702.57 NOK
Capacity	6 TB
Adapter type	Switching
Output voltage	12 V DC
Interface	SATA 6 Gb/s
Maximal load	1 A
Average active efficiency	83 %
Size format	3.5 "
Standard	...	AHD, HD-CVI, HD-TVI, CVBS	AHD, HD-CVI, HD-TVI, CVBS	...
Output power	12 W
Cache memory	256 MB
Sensor	...	1/2.8 " Progressive Scan CMOS	Progressive Scan CMOS	...
Power consumption at no-load	< 0.1 W
Matrix size	...	2.1 Mpx	5 Mpx	...
Number of outputs	1 pcs
Power connectors type	2.1/5.5 mm - Straight plug
Power voltage	100 ... 240 V AC
Technology	<ul style="list-style-type: none"> • ImagePerfect™ firmware is designed to ensure seamless video footage capture in 24x7 surveillance workloads • Built-in data recovery function for uninterrupted video streaming • Increased hard drive workload rate - even up to 180 TB per year • Optimized to handle up to 64 single-stream HD cameras • MTBF (Mean Time Between Faults) : 1 000 000 h
Housing type	Plastic
Designed to continuous operation 24/7	✓
Main features	<ul style="list-style-type: none"> • Short-circuit protection • Overload protection • The device has very small dimensions • Length of the cables : 40 + 15 cm
Operation temp	0 °C ... 40 °C

Resolution	...	<ul style="list-style-type: none"> • 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 25 fps, • 960 x 576 - 960H @ PAL 	2880 x 1620 - 5 Mpx @ HD-CVI @ 25 fps - Aspect Ratio 16 : 9 , 2560 x 1440 - 3.7 Mpx @ HD-CVI / HD-TVI / AHD @ 25 fps , 1920 x 1080 - 1080p @ HD-CVI @ 25 fps , 960 x 576 - 960H @ PAL @ 25 fps	...
Lens	...	2.7 ... 13.5 mm	2.8 mm	...
View angle	...	<ul style="list-style-type: none"> • 107 ° ... 34 (manufacturer data) • 105 ° ... 35 (our tests result) 	<ul style="list-style-type: none"> • 106 ° (manufacturer data) • 101 ° (our tests result) 	...
Range of IR illumination	40 m	...
White light LED illuminator range	...	60 m	40 m	...
IR illuminator power adjustment	Automatic	...
Video output	...	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	...
Audio	...	<ul style="list-style-type: none"> • Microphone built-in, • Audio support via coaxial cable - HD-CVI only 	<ul style="list-style-type: none"> • Microphone built-in, • Audio support via coaxial cable - HD-CVI only 	...
OSD menu	...	OSD menu available via DAHUA recorder	✓	...
Main features	...	<ul style="list-style-type: none"> • Possibility to turn off the LED illuminator • WDR - 130 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • Auto White Balance • AGC - Automatic Gain Control • Mirror - Mirror image • Privacy zones - max. 8 • Sharpness - sharper image outlines 	<ul style="list-style-type: none"> • Smart Dual Illumination technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • D-WDR - Wide Dynamic Range • Auto White Balance • AGC - Automatic Gain Control • ICR - Movable InfraRed filter • BLC/HLC - Back Light / High Light Compensation • 2D-DNR - Digital Noise Reduction • Privacy zones - max. 8 • Mirror - Mirror image • Sharpness - sharper image outlines 	...
Power supply	...	12 V DC / 850 mA	12 V DC / 380 mA	...
Power consumption	...	≤ 10.2 W	≤ 4.5 W	...
Housing	...	Compact, Metal	Dome, Metal	...
Color	...	White	White	...
"Index of Protection"	IP67	IP67	IP67	...
Vandal-proof	...	—	—	...
Operation temp	...	-30 °C ... 60 °C	-40 °C ... 60 °C	...
Weight	0.12 kg	0.78 kg	0.48 kg	0.62 kg
Dimensions	57 x 40 x 26 mm	244 x 91 x 91 mm	Ø 106 x 94 mm	...
Manufacturer / Brand	...	DAHUA	DAHUA	SEAGATE
Guarantee	2 years	3 years	3 years	3 years