

	<a href="#">STRAIGHT PLUG POWER-PLUG/IP54/EPN 250 V 16 A</a>	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE56D0T-IRMMF(3.6mm) - 1080p Hikvision</a>	<a href="#">POE SWITCH WITH BUFFERED POWER SUPPLY IPUPS-16-20-R5U0 16-PORT ATTE</a>
			
	6.83 CAD 6.83 CAD	68.13 CAD 68.13 CAD	835.98 CAD 835.98 CAD
Rated voltage	250 V, 50 / 60 Hz	...	...
Standard	...	AHD / HD-CVI / HD-TVI / PAL	...
Maximal current load	16 A	...	...
Sensor	...	Progressive Scan CMOS	...
Grounding	✓	...	...
Matrix size	...	2.1 Mpx	...
Cable terminals	screw terminals	...	...
Resolution	...	1920 x 1080 - 1080p	...
LAN ports	...	...	<ul style="list-style-type: none"> <li>• 2 x RJ45 10/100/1000 Base-T - Uplink,</li> <li>• 16 x RJ45 10/100 Base-T + PoE (802.3af/at) / Passive PoE</li> </ul>
Range of IR illumination	...	20 m	...
Plug type	CEE 7/6 (Uni-Schuko)	...	...
IR illuminator power adjustment	...	Automatic	...
Lens	...	3.6 mm	...
Management	...	...	—
View angle	...	<ul style="list-style-type: none"> <li>• 82 ° (manufacturer data)</li> <li>• 78 ° (our tests result)</li> </ul>	...
IR illuminator support	...	ICR - Movable InfraRed filter	...
S/N ratio	...	> 62 dB	...
LED diodes	...	...	AC, DC, CHARGING (battery charging), PoE, Gigabit Ethernet
Transmission speed	...	...	<ul style="list-style-type: none"> <li>• 10 / 100 / 1000 Mbps : 2 x Port Uplink,</li> <li>• 10 / 100 Mbps : 16 x Port LAN &amp; PoE</li> </ul>
Video output	...	1 Vpp / 75 Ω - AHD / HD-CVI / HD-TVI, BNC socket	...
Maximal output power	...	...	<ul style="list-style-type: none"> <li>• 40 W @ Passive PoE - LAN1 ... LAN8 ports,</li> <li>• 30 W @ PoE (802.3af/at) - LAN1 ... LAN8 ports</li> </ul>

Main features	...	<ul style="list-style-type: none"> <li>• DNR - Digital Noise Reduction</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Day/night mode</li> <li>• BLC - Back Light Compensation</li> <li>• Auto White Balance</li> </ul>	...
Maximal total power	...	...	130 W
OSD menu	...	—	...
Power consumption	...	≤ 4 W	...
Operation modes	...	...	Standard : 100 m @ 10/100 Mb/s - LAN1 ... LAN8 ports
Housing	...	Dome, Plastic	...
Color	Black (RAL 9005)	White	...
Vandal-proof	...	—	...
"Index of Protection"	IP54	IP44	...
Operation temp	...	-20 °C ... 45 °C	...
SAP Code	...	300609197	...

Main features	...	...	<ul style="list-style-type: none"> <li>• 4K UHD support</li> <li>• The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 16 ports</li> <li>• The modular design streamlines service tasks and enables quick and easy system expansion</li> <li>• The raster system of module assembly facilitates the expansion of the device by further modules</li> <li>• 2 x Place for battery : 12 V / 18 Ah</li> <li>• Battery charging current : 1 A / 2 A - (set with the JP1 jumper)</li> <li>• Battery - Protection against reverse polarity connection, Protection against deep discharge of the battery</li> <li>• Technical outputs of the OC type signaling loss of voltage at the PSU output (OUF) and loss of voltage in the 230V mains (ACF)</li> <li>• PSU thermal protection : 130 °C</li> <li>• Overload protection</li> <li>• LAN &amp; PoE ports - Short-circuit protection, Overvoltage</li> <li>• Can be mounted in a Rack 19" cabinet</li> <li>• "Index of Protection" : IP20</li> </ul>
Power supply	...	12 V DC / 330 mA	190 ... 260 V AC
Weight	0.074 kg	0.15 kg	3.42 kg
Dimensions	100 x 45 x 41 mm	Ø 98 x 66 mm	440 x 220 x 180 mm - RACK 19", 5U
Housing external dimensions	...	...	484 x 225 x 202 mm
Manufacturer / Brand	...	Hikvision	ATTE
Guarantee	2 years	3 years	3 years