


	SWITCH POE BCS-B-SP08G-2SFP 8-PORT SFP BCS BASIC	BUFFERED SWITCHING POWER SUPPLY ADAPTER APS-30-S SATEL	WIRELESS VIDEO DOORBELL ATLO-DBC1-TUYA Wi-Fi, Tuya Smart
			
	158.89 EUR 158.89 EUR	89.12 EUR 89.12 EUR	31.42 EUR 31.42 EUR
Adapter type	...	Switching	...
Sensor	Progressive Scan CMOS - 2 Mpx
Input voltage	...	230 V AC	...
Output voltage	...	12 V DC	...
Resolution	1920 x 1080 px - 1080p
Max. output current (total)	...	3 A	...
LAN ports	• 2 x SFP • 8 x RJ45 (8 x PoE (802.3af/at))
Lens	2.5 mm
Battery charging current	...	0.5 A / 1 A (switchable)	...
Power	...	36 W	...
View angle	• 135 ° (manufacturer data) • 101 ° (our tests result)
Number of outputs	...	3 pcs	...
IR illuminator	10 m
LED illuminator	—
Protections	...	• Short-circuit • Overload	...
Wireless transmission range	The range limited only by the availability of the Wi-Fi network
Wi-Fi standard	IEEE 802.11 b/g/n : 2.4 GHz
Adapter operation control	...	• AC input voltage presence indication AC • Battery status • Battery charging indication	...
Network interface	Wi-Fi : 2.4 GHz
Mobile phones support	The Tuya Smart free application on Android The Tuya Smart free application on iOS
Management	✓
Image compression method	H.264 / MJPEG / JPEG

LED diodes	Power, Link/Act, PoE, System, SFP
Place for battery	...	12V/7Ah	...
Max. battery dimensions	...	151 x 100 x 65 mm	...
Transmission speed	• 10 / 100 / 1000 Mbps - 8 LAN & PoE ports, • 1000 Mbps - 2 SFP ports
Operation temp	...	5 °C ... 40 °C	...
Maximal output power	30 W / port PoE
Maximal total power	96 W
Main features	<ul style="list-style-type: none"> • Micro SD memory cards up to 128GB support (possible local recording), • PIR detector - Motion Detection, Detector range 3 m, • loitering detection • ICR - Movable InfraRed filter • Auto White Balance • AGC - Automatic Gain Control • BLC - Back Light Compensation, • Microphone built-in, • Speaker built-in, • Bidirectional communication, • Noise and echo reduction • Full support via network : WiFi, • Possibility to work in cloud - you don't need to redirect the ports, • Video PUSH personal messaging • Increased battery life • Low current consumption • Operating frequency - Wireless doorbell : 433 MHz
Mount	Surface-mounted



Main features	<ul style="list-style-type: none"> • 2 x Port SFP (Uplink) • 4 operating modes: AI VLAN, AI EXTEND, AI PoE, AI QoS - selectable by switch • AI VLAN mode - ports 1, 2, 3, 4, 5, 6, 7, 8 are isolated from each other, they only have a connection to the Uplink port • AI EXTEND mode - ports 1 ... 8 support transmission up to 250 m (cat5e, cat6) • AI QOS (Quality Of Service) mode - prioritization of video packets • AI PoE mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • ICMP • Support DoS defence • DHCP snooping support • Advanced hardware ACL capabilities to support L2 ~ L4 data stream classification • Port mirroring function • Port forwarding • IGMP Snooping V1/V2 • 802.1p/DSCP traffic priority • Spanning Tree STP/RSTP/MSTP • Multicast • System logs • RESET button • Metal housing 	<ul style="list-style-type: none"> • Output voltage - stabilized • Microprocessor based battery charge control system • Checking the condition of the battery and disconnecting the discharged battery • Ability to work without a battery connected • Acoustic indication of failure • Tamper signaling • LED indication • 2 x OC output 	...
Certificates	CE
Power supply	<ul style="list-style-type: none"> • 48 V ... 56 V DC • 52 V / 1.85 A (power adapter included) 	...	<ul style="list-style-type: none"> • 2 x 18650 battery 3.7 V / 2600 mAh (not included) • 5 V DC - Charging via micro USB port (cable included)
Housing	Waterproof - Plastic
Manufacturer / Brand	BCS BASIC	SATEL	...
Color	White / Black
"Index of Protection"	IP66
Weight	0.68 kg	2.4 kg	<ul style="list-style-type: none"> • 0.084 kg - Wireless Video Doorbell • 0.028 kg - mounting base

Dimensions	225 x 120 x 35 mm	266 x 286 x 100 mm Housing	<ul style="list-style-type: none"> • 142 x 46 x 32 mm - Wireless Video Doorbell • 158 x 62 x 17 mm - mounting base
Guarantee	2 years	2 years	2 years


 DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00