

| | AHD, HD-CVI, HD-TVI, CVBS, TCP/IP, DVR, NVR, 4K, 10/100/1000 Mb/s (LAN & HDMI) | MAINS ADAPTER WITH GROUNDING WS.PLUGS, UNL2 | STRAIGHT PLUG 1E:555234 230V, 3x A, 1.6GRAND | SHELF P19-3U459 70 BACK CABINET 455 mm | SWITCH TL-LS105G 5-PORT TP-LINK | MOUNTING PANEL A10, FRAME | CABLE HDMI 16.5V 1.0 m | ELECTRIC CABLE, KY-5M6.0 | PATCHCORD R451 A, GREEN, 1.0 m | IP SPEED DOME CAMERA OUTDOOR SD5425GA, HNR - 3.7 Mpx 5.4, 135 mm, DMH1A |
|---------------------------------|--|---|---|--|--|---|---|--------------------------|--------------------------------|--|
| | | | | | | | | | | |
| | 1651.71 GBP 1651.71 GBP | 1.68 GBP 1.68 GBP | 7.43 GBP 7.43 GBP | 15.95 GBP 15.95 GBP | 11.38 GBP 11.38 GBP | 9.91 GBP 9.91 GBP | 27.35 GBP 27.35 GBP | 4.61 GBP 4.61 GBP | 6.44 GBP 6.44 GBP | 1653.77 GBP 1653.77 GBP |
| Housing type | | | | | | 1 U Rack 10" | | | | |
| LAN ports | | | | | 5 x (RJ45) 10/100/1000 Mb Auto-Negotiation, Auto MDI/MDX | | | | | |
| Width | | | | 19" | | | | | | |
| Voltage | | 250 V AC | | | | | | | | |
| Max. current | | 16 A | | | | | | | | |
| Sensor | | | | | | | | | | 1/1.8" STARVIS™ CMOS |
| Height | | | 3 U | | | | | | | |
| Protection shutter | | ✓ | | | | | | | | |
| Matrix size | | | | | | | | | | 4 Mpx |
| Maximal current load | | | 32 A | | | | | | | |
| Depth | | | | 455 mm | | | | | | |
| Grounding | | | ✓ | | | | | | | |
| In section | | | | | | | | | | 100 m - Price for 1m when buying a whole roll |
| Connector type | | | | | | | Straight plug HDMI / Straight plug HDMI | | | |
| Electrical cable | | | max. 3 x 6 mm² | | | | | | | |
| Cable | | | | | | | | | | UTP cat. 5e - RJ45 Plug / RJ45 Plug |
| Standard | AHD, HD-CVI, HD-TVI, CVBS, TCP/IP | | | | | | | | | TCP/IP |
| Length of the cable | | | | | | 10 m | | | | |
| Cable terminals | | | | | | | | | | |
| Video inputs | 32 pcs BNC | | | | | | | | | |
| Management | | | | | | | | | | |
| Class of the cable | | | | | | | 26 AWG | | | |
| Length of the cable | | | | | | | | | 1.0 m | |
| Inner conductor | | | | | | | | | | 3 x 6.0 mm² - Cu wire |
| HDMI standard | | | | | | | 2.1 | | | |
| Plug type | | | CEE, 2P+Z | | | | | | | |
| Rated voltage | | | 230 V / 50 Hz | | | | | | | 0.6 / 1 kV |
| LED diodes | | | | | | Power, Link/Act | | | | |
| Video outputs | <ul style="list-style-type: none"> 2 pcs HDMI 4K 1 pcs VGA 1 pcs Video composite (BNC socket) There is a possibility to configure a SPOT function on one of the output | | | | | | | | | |
| Outer coating | | | | | | | | | | Ø 17.2 mm - PVC |
| Transmission speed | | | | | | 10 / 100 / 1000 Mbps - Gigabit Ethernet | | | | |
| Coating color | | | | | | | | | Black | |
| Jumbo Frame | | | | | | 16 kB | | | | |
| MAC addresses table | | | | | | 2 k | | | | |
| Audio inputs | <ul style="list-style-type: none"> 4 pcs BNC 1 pcs BNC - Microphone 12 Channels - Audio support via coaxial cable, HD-CVI only | | | | | | | | | |
| Material | | PVC | Plastic - Polyamide 6 | | | Metal | | | | |
| Main features | | Color : Black | <ul style="list-style-type: none"> Heat resistance : 650 °C (650 °C - housing) IEC/EN 60398-1, IEC/EN 60398-2 compliance Screw-free plug closure Integrated cable gland | | <ul style="list-style-type: none"> LikeWave product series Auto MDI/MDX Auto-learning and Auto-saving functions support for MAC addresses Support for bandwidth control in full duplex (IEEE802.3x) and a back pressure function in half-duplex mode Green TP-LINK technology - big energy saving Box casing designed to wall mounting | | <ul style="list-style-type: none"> Very flexible Gold plated connector prevents the oxidation of contacts | | Very easy and quick assembly | |
| Resolution | | | | | | | | | | 2560 x 1440 - 3.7 Mpx. 2048 x 1536 - 3 Mpx. 2048 x 1296 - 3 Mpx. 1920 x 1080 - 1080p. 1280 x 960 - 1.3 Mpx. 1280 x 720 - 720p |
| Mechanical strength | | | IK09 | | | | | | | |
| Audio outputs | <ul style="list-style-type: none"> 1 pcs BNC 1 pcs BNC - Microphone | | | | | | | | | |
| Certificates | | | | | | | CE, FCC, RoHS | | | |
| Lens | | | | | | | | | | 5.4 ... 135 mm |
| View angle | | | | | | | | | | <ul style="list-style-type: none"> 62° ... 3.6° (manufacturer data) 52° ... 3.4° (our tests result) |
| Operation temp | | | | | | 0 °C ... 40 °C | | | | |
| Optical zoom | | | | | | | | | | x 2.5 |
| Digital zoom | | | | | | | | | | x 16 |
| Permissible relative humidity | | | | | | 10 % ... 90 % | | | | |
| Range of IR illumination | | | | | | | | | | 150 m |
| Video output | | | | | | | | | | |
| Reset rotation speed | | | | | | | | | | <ul style="list-style-type: none"> 400 °/s (horizontal) 300 °/s (vertical) |
| Rotation speed (manual control) | | | | | | | | | | <ul style="list-style-type: none"> 0.1 °/s ... 300 °/s (horizontal) 0.1 °/s ... 140 °/s (vertical) |
| Horizontal rotation range | | | | | | | | | | 360° - continuous |
| Vertical rotation range | | | | | | | | | | 15° ... 90° |
| RS-485 interface | | | | | | | | | | ✓ |
| Number of presets | | | | | | | | | | 300 |
| Horizontal scan | | | | | | | | | | ✓ |
| Route settings | | | | | | | | | | 0 |
| Image compression method | | AI Coding / H.265+ / H.265 / H.264+ / H.264 | | | | | | | | H.265+ / H.265 / H.264+ / H.264 / MJPEG |
| Audio | | | | | | | | | | <ul style="list-style-type: none"> External microphone input Audio output Bi-directional audio streaming support Audio detection |
| Main stream frame rate | | | | | | | | | | 25 fps @ 4 Mpx |
| Network interface | | | | | | | | | | 10/100 Base-T (RJ-45) |
| Image records resolutions | <ul style="list-style-type: none"> AHD / HD-CVI / HD-TVI : 8 Mpx - 3840 x 2160 8M-N - 1920 x 2160 8 Mpx - 2880 x 1920 - HD, CVI only 5 Mpx - 2592 x 1944 4 Mpx - 2560 x 1440 4M-N - 1280 x 1440 3 Mpx - 2048 x 1536 - AHD, HD-TVI only 1080p - 1920 x 1080 720p - 1280 x 720 CVBS : 960H - 960 x 576 IP - max. 12 Mpx - 4000 x 3000 | | | | | | | | | |

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

| | | | | | | | | | | |
|-----------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| Guarantee | 5 years | 5 years | 5 years | 5 years | 5 years | 5 years | 5 years | 5 years | 5 years | 5 years |
|-----------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00