



	AHD, HD-CVI, HD-TVI, PAL CAMERA APTI-H20YS1 PINHOLE - 1080p, 3.7 mm	FRONT MOUNTING BASE USP-UDMK-P FOR SOLAR PANELS	END CLAMP PV-KK/40-50/B FOR SOLAR PANELS 40 mm	OVERVOLTAGE LIMITER AXON-MULTINET-4 ETHERNET	END CLAMP PV-KK/35-50/S FOR SOLAR PANELS 35 mm
					
	383.83 SEK 383.83 SEK	75.20 SEK 75.20 SEK	6.17 SEK 6.17 SEK	1032.43 SEK 1032.43 SEK	4.74 SEK 4.74 SEK
Material	...	Aluminum	Aluminum	...	Aluminum
Number of channels	4	...
Height	40 mm	...	35 mm
Hole diameter	9 mm	...	9 mm
mounting screw	—	...	—
Transmission speed	10 / 100 / 1000 Mbps	...
Standard	AHD, HD-CVI, HD-TVI, PAL
Rated voltage	5 V	...
Maximal voltage	6 V	...
Sensor	1/2.9 " Sony CMOS IMX323
Voltage protection level (line-line)	≤ 40 V - 1 kV/μs [C3]	...
Voltage protection level line-PG	≤ 600 V - 1 kV/μs [C3]	...
Nominal discharge current (line-line)	20 A - 10/1000 μs [C3]	...
Nominal discharge current (line-PG)	20 A - 10/1000 μs [C3]	...
Protection parameters compliance	Compliance with PN-EN61643-21	...
Resolution	1920 x 1080 - 1080p AHD / HD-CVI / HD-TVI , 960 x 576 - 960H PAL
Lens	3.7 mm (pinhole)
Sockets type	8 x RJ-45 shielded socket (8P8C) (4 Inputs, 4 Outputs)	...
Protected pairs of wires	1-2, 3-6, 4-5, 7-8	...
View angle	• 76 ° (manufacturer data) • 66 ° (our tests result)
IR illuminator	✓
Video output	1 Vpp / 75 Ω - AHD, HD-CVI, HD-TVI, PAL
Length of grounding cable	52 cm	...
Audio	• Microphone built-in • Audio output - Cinch socket
Main features	• D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • Sense-UP - (Slow Shutter) - Increase the sensor sensitivity • BLC - Back Light Compensation • Auto White Balance • AGC - Automatic Gain Control • Sharpness - sharper image outlines
OSD menu	✓
Housing	Mini, Plastic	Metal, black	...
Color	Black	...	Black	...	Silver

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Application	The camera is designed for indoor use, due to the possibility of steam condensation.
Power supply	12 V DC / 70 mA
Power consumption	≤ 0.9 W
Operation temp	-20 °C ... 50 °C
Weight	0.06 kg	0.17 kg	0.26 kg	0.31 kg	0.22 kg
Dimensions	62 x 11 x 12 mm	96 x 80 x 73 mm	50 x 43 x 30 mm	162 x 52 x 32 mm	50 x 38 x 28 mm
Manufacturer / Brand	APTI
Guarantee	2 years	2 years	2 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00