





	CONVERTER MODULE DC/DC05-J PULSAR	WIRELESS KEYPAD PRF-LCD-A2 ABAX2 SATEL	POWER CORD CABLE CEE-77/1.5M 1.5 m	ACCESS CONTROL PANEL ACCO-NT2 SATEL
				
	5.69 CAD 5.69 CAD	179.90 CAD 179.90 CAD	5.11 CAD 5.11 CAD	553.94 CAD 553.94 CAD
Support	...	ABAX2 - PERFECTA 64 M
Type	Decreasing the voltage, DC/DC
Frequency band	...	868.0 MHz ... 868.6 MHz
Inputs	<ul style="list-style-type: none"> • 8 pcs - Mainboard inputs • max. 264
Cable	3 x 0.75 mm ² / Angular plug (Schuko)	...
Power voltage	12 V ... 30 V DC
Radio communication range (at open area)	...	< 800 m
Length of the cable	1.5 m	...
Output voltage	12 V DC
Voltage	max. 250 V	...
Output voltage adjustment	—
Output current	0.5 A (max)
Current	max. 10 A	...
Power	6 W (max)
Outputs	<ul style="list-style-type: none"> • 8 pcs - Mainboard inputs • max. 264
Minimal voltage difference between out and in	0 V
Protections	Reverse polarity of the input voltage
Communication	<ul style="list-style-type: none"> • 2 x RS-485 • Expander bus - up to 32 expander modules
Events memory	<ul style="list-style-type: none"> • Events saving to the micro SD card (included) • Recording up to 1 000 000 events from the control panel, • Max. 100 000 events read from each access control module
Users + admins	<ul style="list-style-type: none"> • 8000 + 1 • Max. 65 000 users in the whole ACCO NET system
Application	to cameras powering

Main features	...	<ul style="list-style-type: none"> • Cooperation with the controllers of the ACU-220, ACU-280 series - firmware version 6.06 or later, • Bidirectional encrypted radio communication • Easily readable LCD with backlight displaying detailed information on system state • Keypad backlight buttons, • LEDs indicating device operation state • Quick switch on the selected standby mode by function keys, • Indoor proximity cards and key-fobs reader - Unique EM 125kHz • Alarms: keypad hold-down PANIC, FIRE and AUX • Buzzer for acoustic signaling of some system events • Remote configuration • Remote update of software • Panel communication loss indication • Microswitch as tamper contact • Power-saving mode
Environmental class EN 50130-5	...	II
Output load	<ul style="list-style-type: none"> • OC : 50 mA / 12 V DC • +EX : 0.5 A / 12 V DC • AUX : 0.5 A / 12 V DC
Color	...	White



Main features	<ul style="list-style-type: none"> • Efficiency 86 % • Connectors : Input - 2.1/5.5 mm socket Output - 2.1/5.5 mm plug 	...	<ul style="list-style-type: none"> • Very easy and quick assembly • Solid workmanship 	<ul style="list-style-type: none"> • Support for up to 255 access control modules • Ability to create up to 255 partitions in 1 control panel (up to 255 access control modules can be defined in one partition) • Ability to add up to 16 passageways (up to 16 partitions can be defined in each passageway) • Ability to block/unblock partition at a specified time, or as per access schedule, • Ability to assign 4 identifiers and a keyfob to a single user, • Ability to assign up to 4 proximity cards / DALLAS chips (iButtons) to a user, • Up to 256 access calendars, weekly schedules, daily schedules, time frames • Ability to control the control panel outputs by using keyfobs • Implementation of logic functions on inputs and outputs • Support for turnstiles • Electrical protection of all inputs and outputs as well as communication buses
Power supply	...	<ul style="list-style-type: none"> • Lithium batteries - 2 pcs CR123A 3 V (included) • 5 V DC - APS-055 power adapter (optional) 	...	12 V DC / 140 mA (max)
Battery backup support	—
Operation temp	...	-10 °C ... 55 °C	...	-10 °C ... 55 °C
Permissible relative humidity	93 % (non-condensing)
Weight	0.03 kg	0.24 kg - Without batteries	0.15 kg	0.096 kg
Dimensions	50 x 20 x 18 mm	139 x 124 x 22 mm	...	151 x 69 x 17 mm
Manufacturer / Brand	PULSAR	SATEL	...	SATEL
Guarantee	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00