

| | | |
|--------------------------------|--|---|
| | IP CAMERA BCS-L-TIP12FSR3-AI1 - 1080p 2.8 mm BCS Line | TV OR MONITOR MOUNT BRATECK-PLB-6N |
| |  |  |
| | 86.11 EUR 86.11 EUR | 16.23 EUR 16.23 EUR |
| Standard | TCP/IP | ... |
| Sensor | 1/2.8 " Progressive Scan CMOS | ... |
| Matrix size | 2.1 Mpx | ... |
| Mounting standard | ... | VESA 75, 100, 150, 200, 200x100, 300, 400, 400x200 |
| Resolution | 1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p | ... |
| Lens | 2.8 mm, F1.4 | ... |
| Screen size range | ... | 26 " ... 47 " |
| Bearing capacity | ... | 75 kg |
| Distance from mounting surface | ... | 77 mm |
| View angle | <ul style="list-style-type: none"> • 107 ° (manufacturer data) • 102 ° (our tests result) | ... |
| Range of IR illumination | 30 m | ... |
| Tilt adjustment | ... | -15 ° ... 15 ° |
| Image compression method | H.265+ / H.265 / H.264+ / H.264 / MJPEG | ... |
| Memory card slot | Micro SD memory cards up to 256GB support (possible local recording) | ... |
| RS-485 interface | — | ... |
| Alarm inputs / outputs | — | ... |
| Audio | <ul style="list-style-type: none"> • Microphone built-in • Audio transmission via network | ... |
| Main stream frame rate | 25 fps @ 1080p | ... |
| Network interface | 10/100 Base-T (RJ-45) | ... |
| Network protocols | IPv4/IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, NTP, Multicast, ICMP, IGMP | ... |
| ONVIF | ✓ | ... |
| WEB Server | Built-in | ... |
| Max. number of on-line users | 6 | ... |
| Mobile phones support | Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application BCS Manager • iOS (iPhone): Free application BCS Manager | ... |
| Default IP address | 192.168.1.108 | ... |
| Default admin user / password | admin / - The administrator password should be set at the first start | ... |
| Web browser access ports | 80, 37777 | ... |

| | | |
|----------------------------|---|-------------------|
| PC client access ports | 37777 | ... |
| Mobile client access ports | 37777 | ... |
| Port ONVIF | 80 | ... |
| RTSP URL | rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream | ... |
| Main features | <ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Day/Night mode (color/b&w/auto) • Auto White Balance • AGC - Automatic Gain Control • Possibility to change the resolution, quality and bit rate • Configurable Privacy Zones • Mirror - Mirror image • Motion Detection • Privacy zones • SMD PLUS - searching for an object classified as: human, motor vehicle • IVS analysis : intrusion, crossing the line (tripwire) - classification of people and vehicles | ... |
| Housing | Compact - Metal | ... |
| Color | White | Black |
| "Index of Protection" | IP67 | ... |
| Vandal-proof | — | ... |
| Power supply | <ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 420 mA | ... |
| Power consumption | ≤ 5.1 W | ... |
| Operation temp | -40 °C ... 60 °C | ... |
| Weight | 0.47 kg | 3.11 kg |
| Dimensions | 163 x 70 x 70 mm | 516 x 508 x 77 mm |
| Supported languages | Polish, English | ... |
| Manufacturer / Brand | BCS Line | ... |
| Guarantee | 2 years | 2 years |



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00