




	DOORPHONE PROGRAMMING INTERFACE PRO-USB/2.0 ACO	ACCESS CONTROLLER MC16-PAC-ST-3-KIT ROGER	ACCESS CONTROLLER MC16-PAC-EX-1-KIT ROGER
			
	41.11 EUR 41.11 EUR	661.92 EUR 661.92 EUR	443.31 EUR 443.31 EUR
Compatibility	COMO-PRO, GLASS-PRO monitors
Number of served transitions	...	3 (two-way)	1 (two-way)
Support	RACS 5 v2 (Roger)
Number of supported readers	...	12	4 pcs
Input lines	8 pcs
Number of users	...	unlimited (purchase of the appropriate license required)	...
Output lines	8 pcs
Number of media per ID	...	8 - Proximity card, PIN code, fingerprint, etc.	...
Buffer memory	...	8 000 000 events buffer	...
Number of access zones	...	6	...
Connectors	<ul style="list-style-type: none"> • 1 pcs mini USB - Computer interface • 2 pcs RJ45 Control panel BUS • 3 pcs ARK connectors : system communication line connection: "LINE", power connection: "+DC" and "-DC"
Number of alarm zones	...	6	...
Supported operating systems	Windows
Battery backup support	...	12 V / 20 Ah	max. 7 Ah
Communication	...	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RACS 5 v2 (Roger) • RS-485 interface 	<ul style="list-style-type: none"> • RS-485, • RACS 5 v2 (Roger), • Wiegand
Power supply	...	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC 	230 V AC

Main features	...	<ul style="list-style-type: none"> • Metal housing • The MCX4D I/O expander included • Integrated support in VISO ST software • Functions in the VISO ST system: <ul style="list-style-type: none"> - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system : 128 	<ul style="list-style-type: none"> • Metal housing • Power output : 1 x 0.2 A, 1 x 1.0 A • Power adapter : 24 V DC / 2.2 A, • Battery charging current : 0.3 A • Protection against deep discharge of the battery • Tamper detection - opening the enclosure • Place for battery - 12 V / 7 Ah • Integrated support in VISO EX software • Functions in the VISO EX system: - MSSQL database <ul style="list-style-type: none"> - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system - unlimited - division of the system into partitions operated by independent operators - tool for integration with RACS5 (API) systems - integration with many systems (elevator systems, building applications, SMS, BMS, PSIM, VMS, Active Directory systems)
Operation temp	...	5 °C ... 40 °C	5 °C ... 40 °C
Permissible relative humidity	...	10 % ... 95 % (non-condensing)	10 % ... 95 % (non-condensing)
Weight	0.040 kg	4.08 kg	3.88 kg
Dimensions	71 x 70 x 19.5 mm	405 x 365 x 120 mm	405 x 365 x 120 mm
Manufacturer / Brand	ACO	ROGER	ROGER
Guarantee	2 years	3 years	3 years