




	<a href="#">EXTENSION CABLE WITH FOOT SWITCH SUPLA PNW-01 ZAMEL</a>	<a href="#">ROUTER RUT140 Wi-Fi 2.4 GHz 300 Mbps Teltonika</a>
		
	64.04 AUD 64.04 AUD	85.64 AUD 85.64 AUD
Frequency range	...	2.4 GHz
Application	Lighting control	...
Antenna type	...	SMA-RP socket - without antenna
Wireless	WiFi 2.4 GHz IEEE 802.11 b/g/n	...
Standards	...	IEEE 802.11 b/g/n
Length of the cable	1.5 m / 0.4 m	...
Rated voltage	230 V AC / 50 Hz	...
Mobile phones support	<ul style="list-style-type: none"> <li>• The <a href="#">SUPLA</a> free application on Android</li> <li>• The <a href="#">SUPLA</a> free application on iOS</li> </ul>	...
Radio communication range	The range limited only by the availability of the Wi-Fi network	...
Baud rates	...	11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps
Total maximal current	2.5 A	...
LAN ports	...	1 x 10 / 100 Mbps
WAN interface	...	1 x 10 / 100 Mbps
Maximal total load	350 W - light bulbs and halogen lamps 125 W - CFL fluorescent lamps 60 W - LED bulbs	...
LED indicators	...	Power, WAN, LAN
Power connectors type	<ul style="list-style-type: none"> <li>• 1 x CEE 7/16 - Input</li> <li>• 1 x CEE 7/16 - Output</li> </ul>	...
LTE	...	—
Color	White	...
QSS	...	—
WDS	...	—
DHCP server	...	✓
DDNS	...	Support > 25
Operation modes	...	Access Point, Station

Protections	...	<ul style="list-style-type: none"> <li>• WPA2-Enterprise - PEAP</li> <li>• WPA-PSK/WPA2-PSK</li> <li>• WPA-EAP</li> <li>• WPA3-SAE</li> <li>• WPA3-EAP</li> <li>• OWE</li> <li>• AES-CCMP</li> <li>• TKIP</li> <li>• WEP</li> <li>• EAP-TLS</li> <li>• Auto Cipher modes</li> <li>• Client separation</li> <li>• SSID hiding</li> <li>• MAC addresses filtering</li> <li>• Firewall</li> <li>• Support DDOS, SYN, SSH, HTTP/HTTPS defence</li> <li>• White list / Black list</li> </ul>
Management interface	...	Web browser, Teltonika RMS application
Default IP address	...	192.168.1.1
Operating system	...	RutOS (Linux OS based)
Firmware update	...	✓

Main features	...	<ul style="list-style-type: none"> <li>• Support for Mesh technology,</li> <li>• Compliance with the Modbus, DLMS, DNP3, OPC UA protocol</li> <li>• MDI/MDI-X auto detection feature - auto detecting the data transmission mode</li> <li>• Static / dynamic routing</li> <li>• Support for VoIP technology,</li> <li>• View topology and network status</li> <li>• WMM support (QoS mechanism of the 802.11e standard)</li> <li>• DHCP Relay support</li> <li>• Load balance</li> <li>• Ability to work as a Hotspot,</li> <li>• VLAN support</li> <li>• VPN networks: IPsec VPN, L2TP VPN, PPTP VPN, Open VPN</li> <li>• Compliance with the MQTT protocol</li> <li>• SNMP v1/v2/v3/Trap</li> <li>• Support for IoT (Internet of Things) systems,</li> <li>• Configuration using the Teltonika RMS application</li> <li>• RESET button</li> <li>• Durable aluminum housing</li> <li>• Shock-proof</li> <li>• Industrial wide temperature design.</li> <li>• Mounting on DIN rail,</li> <li>• 3-pin industrial power socket,</li> <li>• Wide range of supported supply voltages</li> <li>• Grounding</li> <li>• "Index of Protection" : IP30</li> </ul>
Certificates	...	CE, UKCA, FCC, WEEE
Power supply	...	<ul style="list-style-type: none"> <li>• 9 ... 30 V DC</li> <li>• 9 ... 30 V DC - Passive PoE, Powering from LAN1</li> </ul>
Power consumption	...	≤ 2 W
Operation temp	...	-40 °C ... 75 °C
Permissible relative humidity	...	10 % ... 90 % (non-condensing)
Weight	0.132 kg	0.15 kg

Dimensions	Ø 73 mm x 32 mm	123 x 69 x 25 mm
Manufacturer / Brand	ZAMEL	Teltonika
Guarantee	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00