



	SOFTWARE RCPM4- WEB-100 ROGER	UNIVERSAL METER UT-125C UNI-T
		
	804.42 EUR 804.42 EUR	24.88 EUR 24.88 EUR
License	RCP Master 4 Web	...
Number of employees	max. 100	...
Time range	12 months	...
Main features	<ul style="list-style-type: none"> • Overview of the working time • Remote registration of T&A events • Employee work history • Registration of remote work • Submitting holiday requests and other types of absence • Verifying of the holiday usage • Displaying the current status of the attendance of employees (present, absent, on a business trip, etc.) • Graphical visualization of employee attendance (attendance list) 	...
Operation	Web browser	...
Supported languages	English, Polish	...
DC voltage measurement	...	400 mV ± (1% + 8) @ 0.1 mV, 4 V ± (0.5% + 5) @ 0.001 V, 40 V ± (0.5% + 5) @ 0.01 V, 400 V ± (0.5% + 5) @ 0.1 V, 600 V ± 0.8% + 5) @ 1 V
AC voltage measurement	...	4 V ± (1.2% + 5) @ 0.001 V, 40 V ± (1.2% + 5) @ 0.01 V, 400 V ± (2.0% + 10) @ 0.1 V, 600 V ± (2.0% + 10) @ 1 V

DC current measurement	...	400 μ A \pm (1.8% + 5) @ 0.1 μ A , 4 μ A \pm (1.8% + 5) @ 0.001 mA , 40 mA \pm (1.8% + 5) @ 0.01 mA , 400 mA \pm (1.8% + 5) @ 0.1 mA
AC current measurement	...	400 μ A \pm (2.0% + 8) @ 0.1 μ A , 4 mA \pm (2.0% + 8) @ 0.001 mA , 40 mA \pm (2.0% + 8) @ 0.01 mA , 400 mA \pm (2.0% + 8) @ 0.1 mA ,
Resistance measurement	...	400 Ω \pm (1% + 5) @ 0.1 Ω , 4 k Ω \pm (1% + 5) @ 0.001 k Ω , 40 k Ω \pm (1% + 5) @ 0.01 k Ω , 400 k Ω \pm (1% + 5) @ 0.1 k Ω , 4 M Ω \pm (1.2% + 10) @ 0.001 M Ω , 40 M Ω \pm (2.0% + 10) @ 0.01 M Ω
Capacitance measurement	...	50 nF \pm (4.0% + 30) @ 0.01 nF , 500 nF \pm (3% + 15) @ 0.1 nF , 5 μ F \pm (4.0% + 10) @ 1 nF , 50 μ F \pm (4.0% + 10) @ 10 nF , 100 μ F \pm (4.0% + 10) @ 100 nF
Inductance measurement	...	—
Frequency measurement	...	9.999 Hz ~ 60 kHz \pm (0.1% + 5) @ 0.001 Hz ~ 0.01 MHz
Square-wave signal duty ratio measurement	...	—
Temperature measurement	...	—
Automatic change of measuring ranges	...	✓
hFE	...	—
Diode test	...	✓
Sound signal of the continuity test	...	✓
Checking TTL logic states	...	—
RS-232	...	—

Main features	...	<ul style="list-style-type: none"> • Large, readable LCD display • Freezing the last reading • Low battery level alarm • Aesthetic and solid construction • Length of the cables - 75 cm
Power supply	...	2 x 1.5V, type AAA/LR03 battery - included
Weight	...	0.164 kg
Dimensions	...	110 x 58 x 35 mm
Manufacturer / Brand	ROGER	UNI-T
Guarantee	...	2 years