



	DOUBLE ROLLER BLIND SWITCH TWO-POSITION DEZ2.01/49-SIMON54 Premium 230 V 6 A	IP CAMERA DS-2CD2T63G2-2I(2.8MM) ACUSENSE - 6 Mpx Hikvision
		
	539.35 NOK 539.35 NOK	2942.62 NOK 2942.62 NOK
Device type	Roller Blind Switch	...
Standard	...	TCP/IP
Rated voltage	230 V AC	...
Sensor	...	1/2.8 " Progressive Scan CMOS
Rated current	6 A	...
Matrix size	...	6 Mpx
Connectors type	screw terminals	...
Application	Flush-mounted, Simon 54 Premium product series, for Nature, Premium frames	...
Backlight	✓	...
Assembly	Claw or screw mounting	...
Main features	<ul style="list-style-type: none"> • The switch allows to direct control of the roller blind motor • Two-position • Pictogram 	...
Resolution	...	3200 x 1800 - 6 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens	...	2.8 mm
View angle	...	107 °
Compression	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Range of IR illumination	...	60 m
Alarm inputs / outputs	...	—
Audio	...	—
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Main stream frame rate	...	<ul style="list-style-type: none"> • 20 fps @ 6 Mpx • 25 fps @ 4 Mpx
Network interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in
Max. number of on-line users	...	6
ONVIF	...	✓

Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Default admin user / password	...	admin / - The administrator password should be set at the first start
Default IP address	...	192.168.1.64
Web browser access ports	...	80
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	...	8000
Port ONVIF	...	80
RTSP URL	...	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization
RS-485 interface	...	—
Main features	...	<ul style="list-style-type: none"> • Camera from AcuSense series • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ROI - improve the quality of selected parts of image • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • SVC (Scalable Video Coding) - technology enabling the transfer of several sub-streams of different quality within one stream • NAS - Network Attached Storage support • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • Configurable Privacy Zones • Possibility to change the resolution, quality and bit rate • Sharpness - sharper image outlines • Day/night mode • ICR - Movable InfraRed filter • Auto White Balance • AGC - Automatic Gain Control • Image rotation and mirror • Filtering of false alarms based on the recognition of persons and vehicles • Intelligent image analysis : crossing the line (tripwire), intrusion - classification of people and vehicles, video tampering, face detection
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 670 mA

Power consumption	...	<ul style="list-style-type: none"> • ≤ 9 W @ PoE (802.3af) • ≤ 8 W @ 12 V DC
Housing	Non-halogen plastic, PC	Compact, Aluminum alloy
Color	Matt black	White + Black
"Index of Protection"	IP20	IP67
Operation temp	...	-30 °C ... 60 °C
Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Italian
Weight	0.084 kg	1.08 kg
Dimensions	<ul style="list-style-type: none"> • 75 x 75 x 44 mm • 31 mm - mounting depth 	Ø 105 x 293 mm
Manufacturer / Brand	KONTAKT Simon	Hikvision
SAP Code	...	311315970
Guarantee	2 years	3 years

