



	<a href="#">IP VANDALPROOF CAMERA TC-C35MS</a> <a href="#">SPEC:I5/A/E/Y/M/H/2.7-13.5MM/V4.1</a> <a href="#">- 5 Mpx 2.7 ... 13.5 mm TIANDY</a>	<a href="#">DUAL SMART SWITCH ATLO-PBRC-WHITE-EWELINK</a> <a href="#">eWeLink</a>
		
	422.80 EUR 422.80 EUR	2.37 EUR 2.37 EUR
Standard	IP	...
Support	...	eWeLink
Frequency band	...	2.4 GHz
Permissible relative humidity	...	10 % ... 90 % (non-condensing)
Resolution	2880 x 1620 - 5 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	...
Sensor	1/2.7 " Progressive Scan CMOS	...
Lens	2.7 ... 13.5 mm - Motozoom	...
View angle	98 ° ... 32 °	...
Range of IR illumination	50 m	...
Image compression method	S+265 / H.265 / H.264	...
Main stream frame rate	25 fps - 5 Mpx 50 fps - 2 Mpx	...
Interface	10/100 Base-T (RJ-45)	...
Alarm inputs / outputs	2 / 1	...
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• Audio input</li> <li>• Audio output</li> <li>• Bi-directional audio streaming support</li> <li>• Audio transmission via network</li> <li>• Compliance with the AAC standard</li> </ul>	...
WEB Server	Built-in	...
Max. number of on-line users	2	...
ONVIF	✓	...
Memory card slot	Micro SD card support up to 512GB	...
Mobile phones support	Port no.: 3000 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">EasyLive Plus</a></li> <li>• iOS (iPhone): Free application <a href="#">EasyLive Plus</a></li> </ul>	...

Access from PC	Port no.: 3000 or access by a cloud (P2P) - PC: Free application <a href="#">Easy7 Smart Client Express</a>	...
Default IP address	192.168.1.2	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80, 443, 3000, 3001, 3002, 23002	...
Mobile client access ports	3000, 3001	...
PC access port	3000, 3001	...
Port ONVIF	80	...
Intelligent image analysis	<ul style="list-style-type: none"> <li>• classification of people and vehicles</li> <li>• video tampering</li> <li>• crossing the line (tripwire)</li> <li>• intrusion</li> <li>• Audio detection</li> <li>• face detection</li> <li>• abandoned/missing object</li> <li>• heat map</li> <li>• people counting</li> <li>• running</li> <li>• parking detection</li> <li>• Detekcja tłumu</li> <li>• Detekcja wałęsania się</li> <li>• protective helmet detection</li> </ul>	...
Main features	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• ICR - Movable InfraRed filter</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• Day/Night mode - configurable</li> <li>• Motion Detection</li> <li>• Privacy zones</li> <li>• Sharpness - sharper image outlines</li> </ul>	<ul style="list-style-type: none"> <li>• LED indication</li> <li>• Programmable buttons</li> <li>• Configuration is done using the mobile application</li> </ul>

Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 750 mA</li> </ul>	2 x 1.5V, type AAA/LR03 battery (not included)
Power consumption	≤ 9 W	...
Housing	Dome - Metal	...
Color	White	White
"Index of Protection"	IP66	...
Mechanical protection class	IK10	...
Operation temp	-35 °C ... 65 °C	...
Weight	0.86 kg	0.06 kg
Dimensions	Ø 143 x 124 mm	86 x 90 x 13 mm
Supported languages	Polish, English, Albanian, Arabic, Spanish, Korean, French, Dutch, Hebrew, German, Portuguese, Russian, Thai, Turkish, Ukrainian, Vietnamese, Italian	...
Manufacturer / Brand	TIANDY	ATLO
Guarantee	3 years	2 years