

	<a href="#">POWER SEPARATOR PFM790 DAHUA</a>	<a href="#">DUAL SMART LED LIGHTING CONTROLLER ATLO-SW2-TUYA Wi-Fi, Tuya Smart</a>	<a href="#">SMART GARAGE DOOR CONTROLLER ATLO-GDC2-TUYA Wi-Fi, Tuya Smart</a>	<a href="#">ACCESS POINT RG-AP840-L Wi-Fi 6, SFP 2.4 GHz, 5 GHz, 547 Mbps + 4804 Mbps RUIJIE</a>	<a href="#">FAN PANEL EPRADO-A19-2W TO RACK CABINET</a>
					
	18.42 EUR 18.42 EUR	11.39 EUR 11.39 EUR	14.84 EUR 14.84 EUR	458.46 EUR 458.46 EUR	30.63 EUR 30.63 EUR
Application	...	switching devices on/off	garage doors	...	...
Assembly	...	...	...	...	in the ceiling of standing cabinets
Number of channels	...	2	...	...	...
Number of fan coolers	...	...	...	...	2 pcs
Input voltage	12 V DC ± 20 %	...	...	...	...
Output voltage	12 V DC ± 5 %	...	...	...	...
Output current	max. 400 mA	...	...	...	...
Maximal total load	...	2 x 150 W	...	...	...
Input socket type	2.1/5.5 mm socket	...	...	...	...
Total maximal current	...	2 x 5 A	...	...	...
Output socket type	2.1/5.5 mm plug	...	...	...	...
Break distance	...	...	3 ... 15 mm	...	...
Number of inputs	1	2	1 x Reed switch	...	...
Current consumption	90 mA	...	...	...	...
Number of outputs	1	2	1 x NO	...	...
Connector type	...	screw terminals	...	...	...
Efficiency	85 % @ 400 mA	...	...	...	...
Wireless	...	• Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n • Bluetooth	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	...	...
Radio communication range	...	< 100 m (open area)	...	...	...
Frequency range	...	...	...	• 2.4 GHz ( 2.4 ... 2.4835 GHz ), • 5 GHz ( 5.150 ... 5.250, 5.250 ... 5.350, 5.470 ... 5.725, 5.725 ... 5.850 GHz )	...
Antenna type	...	...	...	2x2 MU-MIMO - built-in • 3.8 dBi @ 2.4 GHz - 2 pcs  4x4 MU-MIMO - built-in • 4.6 dBi @ 5 GHz - 4 pcs	...
"Index of Protection"	...	IP20	...	...	...
Color	...	White	...	...	Black
Standards	...	...	...	• IEEE 802.11 b/g/n/ax @ 2.4 GHz, • IEEE 802.11 a/n/ac/ax @ 5 GHz	...
Baud rates	...	...	...	547 Mbps @ 2.4 GHz + 4804 Mbps @ 5 GHz	...
LAN ports	...	...	...	• 1 x 100 / 1000 / 2500 / 5000 Mbps Ethernet + PoE IN - RJ45, • 1 x 10 / 100 / 1000 Mbps Ethernet + PoE OUT - RJ45, • 1 x 5 Gbps - SFP	...
Port USB	...	...	...	USB 3.0, 5 V / 1 A	...
LED indicators	...	...	...	Power / System	...
DDNS	...	...	...	—	...
DHCP server	...	...	...	✓	...
Firmware update	...	...	...	✓	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Protections	...	...	...	<ul style="list-style-type: none"> <li>• WEP 64/128-bit, WPA-TKIP, WPA-PSK, WPA2 AES, WPA3-Personal/Enterprise</li> <li>• IEEE 802.1x and Radius Authentication</li> <li>• Black list</li> <li>• Access Control List - ACL package filtering based on source and destination MAC addresses</li> <li>• CPP</li> <li>• NFPP</li> <li>• SSID hiding</li> </ul>	...
Operation modes	...	...	...	Access Point	...
Management interface	...	...	...	<ul style="list-style-type: none"> <li>• Ruijie Cloud Central Management System</li> <li>• Configuration using the Ruijie Reeye application</li> <li>• Remote management</li> <li>• Web browser</li> <li>• Console - RJ-45 output</li> </ul>	...
Mobile phones support	...	<ul style="list-style-type: none"> <li>• The <a href="#">Tuya Smart</a> free application on Android</li> <li>• The <a href="#">Tuya Smart</a> free application on iOS</li> </ul>	<ul style="list-style-type: none"> <li>• The <a href="#">Tuya Smart</a> free application on Android</li> <li>• The <a href="#">Tuya Smart</a> free application on iOS</li> </ul>	Android: Free application <a href="#">Ruijie Reeye</a> iOS (iPhone): Free application <a href="#">Ruijie Reeye</a>	...
Default IP address	...	...	...	192.168.110.1	...
Transmitter power	...	...	...	max. 27 dBm @ 2.4 GHz max. 30 dBm @ 5 GHz	...
Main features	...	<ul style="list-style-type: none"> <li>• Local control by physical button ,</li> <li>• Tuya Smart :</li> <li>• schedule,</li> <li>• timer,</li> <li>• Setting scenarios by different events,</li> <li>• remote access,</li> <li>• voice control ,</li> </ul>	<ul style="list-style-type: none"> <li>• schedule,</li> <li>• timer,</li> <li>• Setting scenarios by different events,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• Magnetic contact included</li> <li>• Garage door open alarm</li> <li>• Opening and closing history</li> <li>• STATUS indicator</li> <li>• ON/OFF button</li> <li>• For indoor use</li> </ul>	<ul style="list-style-type: none"> <li>• Wi-Fi 6 support - a standard that offers higher speeds, better performance in high-traffic environments</li> <li>• OFDMA</li> <li>• MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network</li> <li>• Load balance</li> <li>• WLAN : 32 x BSSID</li> <li>• Multicast</li> <li>• IPv4/IPv6 - Static routing</li> <li>• ICMP</li> <li>• VPN support : IPsec, PPPoE</li> <li>• SNMP</li> <li>• Statistical Reporting, System logs</li> <li>• DHCP client</li> <li>• Bluetooth 5.1 interface</li> <li>• RESET button</li> <li>• Power output : 48 V / 12.95 W PoE OUT / IoT - RJ45</li> <li>• Power output : 5 V / 5 W - USB-A</li> </ul>	...
Housing	...	Plastic	...	Plastic	...
Power supply PoE	...	...	...	Hi-PoE (802.3af/at/bt)	...
Power supply	...	100 ... 240 V AC, 50 / 60 Hz	100 ... 240 V AC, 50 / 60 Hz	<ul style="list-style-type: none"> <li>• 54 V DC / 1.1 A (not included)</li> <li>• PoE / PoE+ / Hi-PoE (802.3bt)</li> </ul>	230 V AC
Power consumption	...	...	...	max. 40 W	...
Operation temp	-30 °C ... 60 °C	-10 °C ... 40 °C	0 °C ... 40 °C	-10 °C ... 50 °C	...
Permissible relative humidity	...	...	...	5 % ... 95 % (non-condensing)	...

Weight	0.032 kg	0.03 kg	0.16 kg	• 1 kg (without bracket) • 1.1 kg (with bracket)	...
Dimensions	108 x 22 x 20 mm	43 x 39 x 22 mm	• 90 x 39 x 25 mm • 5 m (cable length) - Reed switch • 1 m (cable length) - Power supply	230 x 230 x 52 mm (without bracket)	...
Manufacturer / Brand	DAHUA	...	...	RUIJIE	EPRADO
Guarantee	3 years	2 years	2 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00