



	SWITCHING ADAPTER MDR-20-12	EXTENDER HDMI-EX-120- V4
		
	9386.67 HUF 9386.67 HUF	48609.52 HUF 48609.52 HUF
Adapter type	Switching	...
Power voltage	100 ... 240 V AC	...
Output voltage	12 V DC	...
Supported HDMI resolutions	...	480i, 576i, 480p, 576p, 720p, 1080p
Output voltage adjustment	10.8 ... 13.2 V	...
Voltage tolerance	± 1 %	...
Maximal load	1.67 A	...
Output power	20 W	...
Maximal transmission range	...	100 m UTP cat. 5e 120 m UTP cat. 6
Number of outputs	1 pcs	...
Max. number of receivers working in the same time	...	237
Efficiency	80 %	...
Protocols	...	HDBIT
Housing type	DIN	...
Supported HDMI standard	...	1.3
MTBF (Mean Time Between Faults)	236900 hours	...
HDCP	...	1.4
Operation temp	...	0 °C ... 60 °C
Vibration resistance	IEC60068-2-6, 10 ... 500 Hz max. 2 G for 90 minutes	...
Permissible relative humidity	...	10 % ... 90 % (non- condensing)
Power supply	...	5 V DC / 1 A (power adapter included)
Protections	<ul style="list-style-type: none"> • Short-circuit • Overvoltage • Overload protection 	...
Operation temp. / Relative humidity	-20 °C ... 70 °C / < 90 %	...
Weight	0.15 kg	0.13 kg
Dimensions	22.5 x 100 x 90 mm	110 x 58 x 26 mm
Guarantee	3 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00