





	<a href="#">COAXIAL CABLE TRI-LAN-240 50 Ω</a>	<a href="#">EXPANSION PLUG KW-10/5X70 KLIMAS</a>	<a href="#">MULTIMEDIA SHELF AX-RTV1</a>	<a href="#">CABLE FOR SOLAR INSTALLATIONS H1Z2Z2-K-1X4.0/BK</a>
				
	0.95 EUR 0.95 EUR	0.13 EUR 0.13 EUR	9.65 EUR 9.65 EUR	0.92 EUR 0.92 EUR
Number of shelves	...	...	1	...
Bearing capacity	...	...	10 kg	...
Swivel angle adjustment:	...	...	—	...
Color	...	...	Black	...
Material	...	<ul style="list-style-type: none"> <li>• Expansion plug, Polypropylene</li> <li>• Screw, Steel galvanized</li> </ul>	...	...
In section	<b>100 m . Price for 1m when buying a whole roll</b>	...	...	...
Distance from mounting surface	...	...	3 mm	...
Drilling diameter	...	10 mm	...	...
Weight	...	...	1.33 kg	...
Expansion plug length	...	50 mm	...	...
Inner conductor	Ø 1.4 mm Cu ± 0.02 mm Wire	...	...	4.0 mm <sup>2</sup> - Stranded wire Cu - Tin-plated
Dimensions	...	...	300 x 250 x 38 mm	...
Screw dimensions	...	Ø 5 x 70 mm, PZ-2	...	...
Dielectric	Ø 3.8 mm Physical foam	...	...	...
Rated voltage	...	...	...	600 V / 1000 V AC 1800 V DC
Shield	Foil - Al/PET/Al	...	...	...
Application	...	<ul style="list-style-type: none"> <li>• Concrete</li> <li>• Solid clay brick</li> <li>• Solid sand-lime brick</li> </ul>	...	...
Manufacturer / Brand	...	KLIMAS	...	...
Braid	112 x Ø 0.12 mm Stranded wire CuSn	...	...	...
Impedance	50 Ω	...	...	...
Outer coating	Ø 6.1 mm ± 0.02 mm PE	...	...	Ø 5.0 mm - Non-halogen plastic
Coating color	...	...	...	Black

Main features	<ul style="list-style-type: none"> <li>• low attenuation</li> <li>• perfect matched</li> <li>• high screening efficiency</li> <li>• it can be used in WLAN 2,4GHz and 5GHz installations</li> <li>• Operation temp : -40 °C ... 70 °C</li> <li>• Minimal bend radius : 30 / 60 mm</li> </ul>	...	...	<ul style="list-style-type: none"> <li>• UV radiation resistance</li> <li>• Ozone resistance</li> <li>• Hydrolysis resistance</li> <li>• Resistant to oils and aggressive chemicals</li> <li>• Flame resistance (according to VDE 0482-332-2, DIN EN 60332-1)</li> <li>• The insulating layer is made of halogen-free material, which does not produce aggressive fumes during combustion</li> <li>• Increased mechanical strength of the outer coating</li> <li>• Expected lifetime : 25 years</li> </ul>
Cable attenuation at 100m section	Temperature : 20 °C  4.2 dB @ 30 MHz 5.4 dB @ 50 MHz 9.2 dB @ 150 MHz 11.2 dB @ 220 MHz 16.2 dB @ 450 MHz 23.3 dB @ 900 MHz 30.7 dB @ 1500 MHz 33.9 dB @ 1800 MHz 35.9 dB @ 2000 MHz 40.6 dB @ 2500 MHz 65.2 dB @ 5800 MHz	...	...	...
Maximum transmitted power	1.41 kW @ 30 MHz 1.09 kW @ 50 MHz 0.62 kW @ 150 MHz 0.51 kW @ 220 MHz 0.35 kW @ 450 MHz 0.24 kW @ 900 MHz 0.19 kW @ 1500 MHz 0.17 kW @ 1800 MHz 0.16 kW @ 2000 MHz 0.14 kW @ 2500 MHz 0.09 kW @ 5800 MHz	...	...	...
Guarantee	2 years	2 years	2 years	2 years

