




	BATTERY-FREE WIRELESS DOORBELL WITH 230V AC OUTLET WDP-91H2 AC 230V EURA	IP SPEED DOME CAMERA OUTDOOR OMEGA-21P22-6 2.1 Mpx - 1080p 3.9 ... 85.5 mm	MOUNTING PROFILE USP-SM-1100 FOR SOLAR PANELS
			
	24.44 EUR 24.44 EUR	242.10 EUR 242.10 EUR	13.97 EUR 13.97 EUR
Standard	...	TCP/IP	...
Material	Aluminum
Sensor	...	1/2.7 " Sony CMOS	...
Signaling mode	Sound signaling
Number of ring-tones	58
Matrix size	...	2.1 Mpx	...
Volume adjustment	max. 85 dB / 1 m
Operation range	max. 100 m in open area
Frequency band	433.92 MHz
Main features	<ul style="list-style-type: none"> • The doorbell button is powered by an electromagnetic transducer, does not require any battery • Wireless doorbell + 1 grounded outlet 16A/250V CEE 7/5
Resolution	...	1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p , 720 x 576 - D1 , 720 x 480 640 x 480	...
Scanning system	...	Progressive	...
Lens	...	3.9 ... 85.5 mm	...
Manufacturer / Brand	EURA
View angle	...	<ul style="list-style-type: none"> • 65 ° ... 4.2 ° (manufacturer data) • 51 ° ... 4.2 ° (our tests result) 	...
Optical zoom	...	x 22	...
Auto IR illuminator	...	Adaptive adjusting of the IR illuminator power to the lens zoom and outdoor light conditions	...
Range of IR illumination	...	50 m	...
S/N ratio	...	≥ 50 dB (AGC off)	...
Video output	...	—	...

Rotation speed (manual control)	...	1 °/s ... 45 °/s (horizontal) 1 °/s ... 30 °/s (vertical)	...
Horizontal rotation range	...	360 ° continuous	...
Vertical rotation range	...	0 ° ... 90 °	...
RS-485 interface	...	—	...
Number of presets	...	255	...
Horizontal scan	...	✓	...
Image compression method	...	H.264 / MJPEG	...
Protections	...	Overvoltage	...
Alarm inputs / outputs	...	—	...
Network interface	...	10/100 Base-T (RJ-45)	...
Network protocols	...	TCP/IP, HTTP, HTTPS, IGMP, DDNS, SMTP, FTP	...
Bitrate	...	128 ... 5120 kbps	...
WEB Server	...	Built-in	...
ONVIF	...	2.4	...
Mobile phones support	...	Connection in cloud technology only • Android: Free application Cloudlens • iOS (iPhone): Free application Cloudlens	...
Default IP address	...	192.168.1.110	...
Default admin user / password	...	admin / admin	...
Web browser access ports	...	80	...
Port ONVIF	...	8999	...
RTSP URL	...	rtsp://ip_address/1/h264major - Main stream rtsp://ip_address/1/h264minor - Sub stream rtsp://ip_address:554/1/mjpeg - Sub stream	...
Route settings	...	3	...
OSD menu	...	✓ preset 95	...

Main features	...	<ul style="list-style-type: none"> • DIS - Digital Image Stabilization • F-DNR (Defog) - Reduction of image noise caused by precipitation • Parking action - this function enables to locate the camera to specific position automatically if operator doesn't operate the controller for some time • WDR - Wide Dynamic Range • ICR - Movable InfraRed filter • BLC - configurable Back Light Compensation • 3D-DNR - Digital Noise Reduction • Auto White Balance • Day/Night mode (color/b&w/auto) • IR illuminator optimization • Mirror - Mirror image • Motion Detection - Split the screen into zones 22 x 18 • Privacy zones - max. 4 • ROI - improve the quality of selected parts of image 	...
Power supply	<ul style="list-style-type: none"> • 230 V AC - Wireless doorbell, • Electromagnetic transducer - Doorbell button 	12 V DC / 3 A (power adapter included)	...
Housing	...	Speed Dome, Metal	...
Color	...	White / Black	...
"Index of Protection"	<ul style="list-style-type: none"> • IP55 - Doorbell button • IP20 - Wireless doorbell 	IP66	...
Operation temp	<ul style="list-style-type: none"> • -18 °C ... 40 °C - Doorbell button • 0 °C ... 45 °C - Wireless doorbell 	-20 °C ... 60 °C	...
Weight	<ul style="list-style-type: none"> • 0.044 kg - Doorbell button • 0.1 kg - Wireless doorbell 	1.54 kg (with bracket)	0.21 kg
Dimensions	<ul style="list-style-type: none"> • 38 x 85 x 23 mm - Doorbell button • 62 x 102 x 74 mm - Wireless doorbell 	200 x 246 x 136 mm (with bracket)	1100 x 50 x 50 mm
Supported languages	...	English, Chinese	...
Guarantee	2 years	2 years	2 years